

## Abide


|                        |  |                                 |
|------------------------|--|---------------------------------|
| Collection             | <b>Abide &amp; Inhabit</b>   |                                 |
| Style Number           | <b>4107V</b>   |                                 |
| Construction           | <b>Heavy Commercial Luxury Vinyl Tile</b>  |                                 |
| Class / ASTM resilient |  |                                 |
| Finish                 | <b>ExoGuard+®</b>  |                                 |
|                        | U.S.   | Metric                          |
| Nominal Dimensions     | <b>7 in w x 47 in l</b>  | <b>18 cm w x 120 cm l</b>       |
| Actual Dimensions      | <b>7.09 in w x 47.24 in l</b>  | <b>18.01 cm w x 119.99 cm l</b> |
| Wear Layer Thickness   | <b>F1700</b>   |                                 |
| Overall Thickness      | <b>0.098 in</b>  | <b>2.5 mm</b>                   |
| Edge Profile           | <b>Squared Edge</b>  |                                 |
| Installation Type      | <b>Dry Back</b>  |                                 |
| Installation           | <b>Direct Glue</b>   |                                 |
| Recommended Adhesive   | <b>LokWorx Resilient, SHAW 4100 4 GAL, S150 SPRAY ADHS, LokWorx+ Resilient or 4151</b> |                                 |



### Packaging

|                   |                    |                  |
|-------------------|--------------------|------------------|
| Pieces per Carton | <b>18 pcs</b>      |                  |
| Area per Carton   | <b>41.85 sq ft</b> | <b>3.89 sq m</b> |
| Weight per Carton | <b>38.64 lbs</b>   | <b>17.53 kg</b>  |

### Recommended Installation Method



### Coordinating Products

Sheet: Inhabit Sheet

### Performance + Testing

|   |   |  |
|---|---|--|
| Static Load (ASTM F970)                               | <b>Passes (Modified), *1500 lbs</b>   | *This test is intended to compare relative properties of different styles and constructions. Results are based on a laboratory test and used for comparative purposes - real life load limit may vary. |
| Residual Indentation (ASTM F1914)                     | <b>Passes</b>   |  |
| Resistance to Heat (ASTM F1514)                       | <b>Passes</b>   |  |
| Resistance to Light (ASTM F1515)                      | <b>Passes</b>   |  |
| Resistance to Chemicals (ASTM F925)                   | <b>Passes</b>   |  |
| Smoke Density (ASTM E662, Flaming Mode)               | <b>Passes</b>   |  |
| Radiant Panel (ASTM E648)                             | <b>Passes, Class I</b>  |  |
| Coefficient of Friction (ASTM D2047, Slip Resistance) | <b>&gt;0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes</b> |  |

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties

[15 Year Commercial Limited Warranty](#)

## Diversity, Equity & Inclusion

We believe all humans are equal. Individually and collectively, we need to proactively create and promote opportunities that give everybody an equal footing in life. We nurture an environment where every voice and perspective can be heard, and proactively promote accessibility and inclusivity inside our network and beyond. One proof point is our ability to meet the criteria of the Social Fairness pillar of the Cradle to Cradle Product Standard. At Shaw Industries, we promote supplier participation that is reflective of Shaw's diverse customer base and local community. More than 42% of our spend\*\*\*\* is with small and diverse businesses. We believe having a strong Supplier Diversity Program is strategic for bringing more innovation to our businesses and opening new markets for growth.

## Material Health & Environmental Certifications

### Health & Wellbeing

Material Ingredient Transparency

[Health Product Declaration \(HPD\) | 100 ppm Disclosure](#)

### Climate Impact

Environmental Product Declaration (EPD)

[3rd Party Certified in Accordance with ISO 14025, EN 15804, & ISO 21930:2017](#)

Total Recycled Content

0% (Pre-Consumer 0% | Post-Consumer 0%)

### Global Product Assessment

[FloorScore® | Certified](#)

CE Marking (EN 14041) | 3rd Party Certified

Country of Origin | Imported

## Leed v4 Contribution Credits

MR Credit: Building Product Disclosure and Optimization  
Environmental Product Declarations - Option 1: Environmental Product Declaration

**RFCi Industry Average EPD (50%)**

EQ Credit: Low Emitting Materials  
Option 1: Product Category Calculations

**FloorScore Certified**

<https://pdmsview.shawinc.com/viewer/doc/455>

[Maintenance Guidelines](#)

Please visit [www.shawcontract.com](http://www.shawcontract.com) for the most current warranty information. Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.

\*\*\*\*Allowable spend is domestic (US) spend in categories in which we have diverse suppliers from which to choose. Compared to non-allowable spend which includes categories in which we do not have domestic, small or diverse suppliers available to meet our needs.

Visit [shawcontract.com/testing](http://shawcontract.com/testing) for more information.

