

R | **Admix 18x36** PRODUCT SPECIFICATIONS



COLLECTION	Admix
STYLE NUMBER	I508V
CONSTRUCTION	Solid Vinyl Tile
OVERALL THICKNESS	0.126 inches (3.2 mm)
EDGE PROFILE	Squared Edge
REFERENCE SPECIFICATION	ASTM F1700 Class I monolithic solid vinyl tile Type A (smooth)
INSTALLATION TYPE	Dry Back
INSTALLATION	Glue Down
RECOMMENDED ADHESIVE	LOKWORX RESILIENT, LOKWORX+ RESILI, LOKWORX+ RESILIENT or 4151
INSTALLATION STATEMENT(S)	AdMix offers a virtually seamless design when installed correctly and does not require directional arrows when installing.

Packaging

PLANK SIZE

PIECES /BOX

AREA /BOX

WEIGHT /BOX

US Units

18 inches W x 36 inches L

12

54 sq ft

64.8 lbs

Metric Units

45.7 cm W x 91.4 cm L

5 sq m

29.4 kg

Performance Testing

STATIC LOAD / ASTM F970

Passes (Modified), *2500 lbs

RESIDUAL INDENTATION / ASTM F1914

Passes

RESISTANCE TO CHEMICALS / ASTM F925

Passes

RADIANT PANEL / ASTM E648

Passes, Class I

SMOKE DENSITY / ASTM E662

Passes

SLIP RESISTANCE / ASTM D2047

≥0.5, meets the recommended static coefficient of friction for ADA walking surfaces

*Results are based on a laboratory test and used for comparative purposes. Real life load limit may vary.

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

R | Admix 18x36

Warranty

25 Year Limited Commercial.

Commercial Limited Underbed Bond Shaw Lockworx+ Resilient, Shaw 4151.

Please visit patcraft.com for the most current warranty information.