

## BARRALI II AH113

### PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Barrali II / AH113
PRODUCT TYPE	LVT
CONSTRUCTION	Luxury Vinyl Tile
WEAR LAYER THICKNESS	20 mil (0.5mm)
INSTALLATION METHOD	GlueDown
GAUGE	2.5 mm
FINISH	M-Force™ Ultra
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
FLEXIBILITY	ASTM F137 - Passes - 1" mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM F1514 - Passes - $\Delta E < 8$
CRITICAL RADIANT FLUX	ASTM E648 - Class 1 ( $> 0.45 \text{ W/cm}^2$ )
SMOKE DENSITY	ASTM E662 Part A - Less than 450
CERTIFICATION	FloorScore® Certified
INSTALLATION	Glue Down
WARRANTIES	Limited 20 Year M-Force Ultra Commercial Warranty Limited 20 Year M-Force Ultra Commercial Warranty