CRACKLED





CRACKLED



CRACKLED Style Name Collection Name Surface Works

Style Number 54871

Product Type **Carpet Tile**

Construction Multi-Level Pattern Loop 100% Eco Solution Q® Nylon Fiber

Dye Method Solution Dyed Synthetic Primary Backing Strataworx Secondary Backing Traffic Rating Heavy

Protective Treatments SSP Shaw Soil Protection

> U.S. Metric

Product Size 24 in x 24 in 60.96 cm x 60.96 cm

80 ft2 Area Per Carton 7.43 m²

Pieces Per Carton 20


Gauge 1/10 in 39.37 per 10 cm Stitches 10 per in 39 per 10 cm Finished Pile Thickness 0.088 in 2.24 mm

Average Density 6545 oz/yd3

Total Thickness 0.23 in 5.84 mm Tufted Weight 16 oz/yd² 542.5 g/m²



Recommended Installation Methods



Performance Testing

Pill Test **Pass** Radiant Panel Class I

NBS Smoke Less than 450 Less than 3.5 kv **Electrostatic Propensity**

CRI Greenlabel Plus GLP2671

ADA Compliance >0.6. meets the recommended static coefficient of friction

for ADA walking surfaces and accessible routes

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Warranties

Carpet Tile 15 year Commercial Limited Warranty with Stain and Color for StrataWorx

Environmental

Recycled Content Pre-consumer - 24%, Post-consumer - <1%

> Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

