


## First Step II

Collection	Tuff Stuff II
Style Name	First Step II
Style Number	GT315
Product Type	Carpet Tile
Size	24" X 24"
Construction	Tufted
Installation	Brick Ashlar, Quarter Turn




Feature	Description
Minimum Sq Yard	No minimum
SQ Yrds per carton	6.22
Pounds per Carton	58.38
Backing Material	EcoFlex NXT
Installation Methods	Brick Ashlar, Quarter Turn
Stitches per Inch	8.5 (33.46 per 10cm)
Density	6739
Tufted Pile Weight	38.00 oz/yd2 (1288 g/m2)


## Recommended Installation Methods




Brick Ashlar



Brick Ashlar



Brick Ashlar



Quarter Turn

## Colorways



### Walnut

Color code: 859  
Style number: GT315



### Cobalt

Color code: 955  
Style number: GT315



### Iron Ore

Color code: 983  
Style number: GT315



### Obsidian

Color code: 989  
Style number: GT315

## Performance

Feature	Description
Foot Traffic Recommendation TARR	Severe
Flammability	ASTM E 648 - Class 1 (Glue Down)
Smoke Density	ASTM E 662 - Less than 450
Static Propensity	AATCC - 134 Under 3.5 KV
Soil Release Technology	EcoSentry Soil Protection

## Sustainability

Feature	Description
Beyond Carbon Neutral	This product is 100% carbon neutral plus an additional 5% offset
Carbon Handprint	-0.103 kg CO2e/ft2
Embodied Carbon	2.06 kg CO2e/ft2
Total Recycled Content	53%
Pre-Consumer Recycled Content	53%
NSF 140	<a href="#">EcoFlex NXT - NSF 140 Gold</a>
Indoor Air Quality	GLP 1098
TVOC Range	0.5 mg/m3 or less
Red List Free	True
Mindful Materials	Participates in Mindful Materials Library
Environmental Product Declaration	<a href="#">EPD EcoFlex NXT</a>
Health Product Declaration	<a href="#">HPD 2.1 EcoFlex NXT Gold - 1000 ppm</a>
Environmental Claims Validation	<a href="#">EPD EcoFlex NXT</a>
LEED Credit Potential	LEED Eligible
Living Product Challenge	Living Product Challenge 2.0