



# 7068 CALATRAVA



## Wear

---

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.



## Backing Performance

---

Kraus carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



## ASTM E648 Class I

---

This product has passed the standard test method for critical radiant flux of floor-covering systems using a radiant heat energy source and meets the standards as defined within ASTM E648.



## Lifetime Warranty

---

- Commercial Wear
- Backing Performance



01 | Lithograph



03 | Oil Print



04 | Transfer Grey



05 | Acrylic Mode



06 | Graphite



07 | Watercolor

## specifications

Supplier	Kraus®	
Fiber system	100% BCF Solution dyed nylon 6,6	
Construction	Scroll loop	
Backing system	FiberCore™ Modular	
Pile weight	18 oz./y <sup>2</sup>	610 g/m <sup>2</sup>
Pile height	0.12"	3 mm
Gauge	1/12	42.2 rows/10 cm
Stitches	10.0 s.p.i.	39.4 stitches/10 cm
Density	6400	7.44 kilotex/cm <sup>2</sup>
Stain resistance	8.0 (AATCC 175)	
CRI/CCI air quality test	Green Label Plus	GLP 2116
Environmental awareness	Eligible for any recycling program	
Static generation	3.0kV or less (AATCC 134)	
Flammability	ASTM E648 – Class I (direct glue) DOC FF 1-70	
Colorfastness to light	5 (AATCC 16)	
Modular size (w x l)	19.7" x 19.7"	50 cm x 50 cm
Packaging	20 tiles/carton 53 lbs/carton	6 y <sup>2</sup> /carton 28 cartons/pallet
Recommended adhesive	Kraus I Premium Adhesive™ KPA-301	
Installation method	Quarter-Turn and Brick	
Lifetime Warranties (See full text for details)	Commercial Wear Backing Performance	

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. Product image colours may vary due to print processes and monitor display settings. To ensure that the installation meets the manufacturers requirements please note that Kraus Premium Adhesive is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. See [krausflooring.com](http://krausflooring.com) for latest specifications.

E&OE.

1607