



COORDINATES WITH
7241
ELEMENTS

7240 PERSPECTIVE



Stain Proof – No Exceptions™

Perfecting the balance between dye technology and understanding a fiber's construction, our carpets feature a Stain Proof – No Exceptions warranty. Most spills can be easily removed through gentle blotting allowing your carpet to remain beautiful in spite of life's little mishaps.



Backing Performance

Kraus carpet tiles are manufactured to provide dimensional stability and will not delaminate from face fiber or edge ravel. Our Backing Performance warranty guarantees that the backing on this product will not shrink, grow, cup or dome, which ensures easy installation and product longevity.



Wear

Our carpet is guaranteed to withstand the wear and tear of daily life. Built to perform, Kraus carpet offers strength from face fiber to secondary backing.



10 Year Warranties

- Stain Proof – No Exceptions™
- Commercial Wear
- Backing Performance



04 | Contrast



01 | Form



05 | Scale



02 | Shape



06 | Texture



03 | Attribute



07 | Balance

specifications

| | | |
|---|---|---|
| Supplier | Kraus® | |
| Fiber system | 100% BCF Polypropylene | |
| Construction | Multi level loop | |
| Backing system | EuroBac™ Modular | |
| Pile weight | 20 oz./y ² | 680 g/m ² |
| Pile height | 0.13"/0.18" | 3.3 mm/4.5 mm |
| Gauge | 1/12 | 47.3 rows/10 cm |
| Stitches | 11 s.p.i. | 43.3 stitches/10 cm |
| Density | 4800 | 12.8 kilotex/cm ² |
| CRI/CCI air quality test | Green Label Plus | GLP 1097 |
| Environmental awareness | Eligible for any recycling program | |
| Recycled content | EuroBac™ Modular Backing – min. 20% pre-consumer | |
| Static generation | 3.0 kV or less (AATCC 134) | |
| Flammability | ASTM E648 – Class I (direct glue) DOC FF 1-70 – passes ASTM E662 - < 450 (flaming mode) | |
| Colorfastness to light | 5.0 (AATCC 16) | |
| Modular size (w x l) | 19.7" x 19.7" | 50 cm x 50 cm |
| Packaging | 20 tiles/carton 46 lbs/carton | 6 y ² /carton 32 cartons/pallet |
| Recommended adhesive | Kraus Premium Adhesive™ KPA-301 | |
| Installation method | Monolithic, Quarter-Turn, Ashlar and Brick | |
| 10 Year Warranties (See full text for details) | Stain Proof – No Exceptions™ Commercial Wear Backing Performance | |

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. Product image colours may vary due to print processes and monitor display settings. To ensure that the installation meets the manufacturers requirements please note that Kraus Premium Adhesive is the recommended and required adhesive for this product. Failure to use this adhesive may void any warranty related claims. Please see installation instructions for full details. See krausflooring.com for latest specifications.

E&OE.

1710