


## Transfiguration 2.5

### Overview


Feature	Description
Collection	Hot and Heavy II
Style	Transfiguration 2.5 (C2087)
Product Type	LVT
Size	18 in x 36 in
Construction	Flexible LVT
Total Thickness	2.5 mm
Wear Layer	20 mil (0.5mm)
Finish	M-Force Ultra
Surface Profile	Embossed
Installation	Glue Down
Installation Method	Brick Ashlar, Herringbone, Monolithic, Random
Recommended Adhesive	M95.0, M99, MS160, M700 Plus, or Total Bond Adhesive



### Recommended Installation Methods



Brick Ashlar



Herringbone

### Colorways



#### Reshape

Color code: 825A  
Style number: C2087



#### Modify

Color code: 828A  
Style number: C2087



#### Variation

Color code: 859A  
Style number: C2087



#### Shift

Color code: 929A  
Style number: C2087



#### Alter

Color code: 969A  
Style number: C2087

## Testing

Feature	Description
Classification	(ASTM F1700) Class III, Type B - Embossed
Squareness	(ASTM F2421) Passes - $\pm 0.10''$ max
Size and Tolerance	(ASTM F2421) Passes
Thickness	(ASTM F386) $\pm 0.005''$
Flexibility	(ASTM F137) Passes
Dimensional Stability	(ASTM F2199) Passes
Static Load Limit	(ASTM F970) Passes, modified at 1000 psi
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes
Resistance to Light	(ASTM F1515) Passes
Resistance to Heat	(ASTM F1514) Passes
Radiant Flux	(ASTM E648) Class 1
Smoke Density	(ASTM E662) = 450
Wear Layer Thickness	20 mil (0.5mm)
Lightfastness	(ASTM F1515) Passes

## Sustainability

Feature	Description
Specify for a Cure	Eligible

## Packaging

Feature	Description
Pieces per Carton	12
Weight per Piece (lbs)	3.9
Cartons Per Pallet	48
Square Feet per Carton	53.99
Weight per Carton (lbs)	46.5