

PARISH AH034

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Parish / AH034
PRODUCT TYPE	Ultimate Flex
COLLECTION NAME	Parish
CONSTRUCTION	Luxury Vinyl Tile
THICKNESS	ASTM F386 - Passes - as specified ± 0.005 "
WEAR LAYER THICKNESS	10 mil
GAUGE	2 mm
FINISH	Urethane Finish
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
SIZE AND TOLERANCE	Tile ASTM F2055; Plank ASTM F2421 - Passes - ± 0.016 "/linear foot
FLEXIBILITY	ASTM F137 - Passes - 1" mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
SLIP RESISTANCE	ASTM C1028 - Passes - Wet: greater than/equal to 0.5
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dylling, surface attack or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM E649 - Class 1 (> 0.45 W/cm ²)
CRITICAL RADIANT FLUX	ASTM E649 - Class 1 (> 0.45 W/cm ²)
SMOKE DENSITY	ASTM E662 Part A - Less than 450
CERTIFICATION	FloorScore® Certified
INSTALLATION	Glue Down
WARRANTIES	6 Year Limited Commercial Warranty 25 Year Limited Residential and Multifamily Warranty