

RECONNECTED AH100

PRODUCT SPECIFICATIONS

STYLE NAME / NUMBER	Reconnected / AH100
PRODUCT TYPE	LVT
CONSTRUCTION	Luxury Vinyl Tile
INSTALLATION METHOD	GlueDown
GAUGE	2mm
SIZE	6" x 48"
FINISH	Enhance Urethane
CLASSIFICATION	ASTM F1700 - Class III, Type A - Smooth, Type B - Embossed
SQUARENESS	ASTM F 2421 - Passes - ± 0.10 " max
SIZE AND TOLERANCE	Tile ASTM F2055; Plank ASTM F2421 - Passes - ± 0.016 "/linear foot
FLEXIBILITY	ASTM F137 - Passes - 1" mandrel
DIMENSIONAL STABILITY	ASTM F2199 - Passes - 0.020"/linear foot max
RESIDUAL INDENTATION	ASTM F1914 - Passes - Average less than 8% maximum single reading 10%
RESISTANCE TO CHEMICALS	ASTM F925 - Passes - No more than a slight change in surface dylling, surface attack or staining
RESISTANCE TO LIGHT	ASTM F1515 - Passes - $\Delta E < 8$
RESISTANCE TO HEAT	ASTM E649 - Class 1 (> 0.45 W/cm ²)
SMOKE DENSITY	ASTM E662 Part A - Less than 450
OPTIONAL UNDERLAYMENT	Mohawk AccuSound™ -Loose lay - Active Sound-Click
CERTIFICATION	FloorScore® Certified
WARRANTIES	Limited 10 Year Commercial Warranty Limited 25 Year Residential Warranty