

APPLICATION DATA SHEET



ENVIROGRAF®

AP042-ENV/HS-10-2019

Product Number: 42

ENV/HS High-Density Clear Lacquer

Description:

High-density clear lacquer for use over HW02N or ES/VFR

Coverage:

Approximately 11m² per litre per coat. A second coat may be required for areas subject to hard wear.

Preparation and Application:

Ensure that the surface to be coated is completely clear and dry before applying ENV/HS.

Stir well before application. May be applied using brush or spray. The result is dependent on the condition of the substrate and temperature of application. Thinners can be used if necessary. Drying time is approximately 2 – 4 hours.

Tools and Storage:

Clean tools and spillages immediately with thinners.

Keep containers in a dry, cool, well ventilated space away from heat. Containers must be kept tightly closed and stored at a minimum temperature of 5°C and a maximum temperature of 35°C.

Precautions:

- Highly flammable. Keep away from sources of ignition: no smoking
- Ensure good ventilation during application and drying. Do not inhale vapour or spray mist
- Avoid contact with skin and eyes. Wear suitable protective clothing including gloves and eye/face protection
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner. Do not use solvent or thinners.
- If swallowed seek medical advice immediately.
- Keep out of the reach of children.
- Dispose of this material and container only to a waste collection point dealing in hazardous or special waste. Avoid release to the environment