

APPLICATION DATA SHEET



ENVIROGRAF®

AP064-10-2012

Product Number: 64

Woodfiller

This product is a water-based general purpose wood filler.

PHYSICAL DATA:

Type:	Water-based
Colour:	Natural
Viscosity:	Paste
Specific Gravity:	1.40

RECOMMENDATION FOR USE:

Application methods:	Putty Knife or paint scraper
Conditions during application:	Temperature of air and substrate must be above 5 °C.
Drying time:	Variable depending on thickness and ambient conditions.
Coverage:	100ml per 140 grams

MISCELLANEOUS:

Size of containers:	250ml , 500ml and 1 litre
Remarks:	Frost-free freight and storage. STIR WELL before use
Shelf Life:	12 months in unopened original packaging (Stored between 5-30 °C)

DIRECTIONS FOR USE:

It is advisable to wear gloves, although the is non-toxic, safe handling practices should still be

Implemented to avoid irritating sensitive skin.

If glue makes contact with eyes, flush thoroughly with water for at least 15 minutes.

Seek medical attention. For skin wash with soap and water.

The surface must be clean, free from all loose materials, dust, dirt, oil and any other contaminants.

Apply with a putty knife or paint scraper by pasting over the hole or crack.

For deep holes apply Woodfiller in several layers, allowing each layer to dry between applications.

Larger applications may shrink and crack on drying. Re-apply Woodfiller.

Clean tools with water.