

APPLICATION DATA SHEET



ENVIROGRAF®

AP084-S/CP/Card-02-2019

Product Number: 84 S/CP/Card

Description:

A material applied to ceilings and walls using CA/N adhesive. Supplied in 1000mm width to any length. For use on lath-and-plaster walls and ceilings needing fire protection upgrades.

Application:

- Clean off any existing wall or ceiling paper
- Scrape off any loose paint. If gloss paint rub down with glass paper.
- Ensure that all distemper is removed from the ceiling and that distemper is not under existing coatings.
- Also ensure the cleaned off ceiling is sealed with Product 93 (Stabond) to ensure the adhesive does not dry out due to the ceiling absorbing moisture.
- Cut the Envirograf® S/CP/Card to length.
- Applying Envirograf® S/CP/Card to ceilings is a two-person job. One applies the adhesive with a comb float whilst the other person applies the Envirograf® card.
- Apply a coat of CA/N adhesive to the ceiling using a serrated edge applicator (as used when wall tiling).
- To press the Envirograf® S/CP/Card onto the ceiling (grey side affixed to ceiling) it is best to use a wide flat clean scraper and roll with a wallpaper roller.
- Approximate coverage of CA/N is 3m² per litre.
- If the ceiling is clean, two people could apply approximately 20 linear metres of Envirograf® card in 90-120 minutes.
- Give the adhesive time to dry before coating. Emulsion or other paints can be applied after 2-3 hours.
- **NOTE** – The grey side of the Envirograf® card is affixed to the ceiling, with the white side down for decorating.

Butt together the edges of the card and lightly roll over the edges with a wallpaper roller, ensuring a clean finish.