

APPLICATION DATA SHEET



ENVIROGRAF®

AP093-03-2015

Product Number: 93

Stabond stabilising bonding/sealing liquid

Description:

Transparent water based bonding/sealing liquid for porous/friable surfaces such as plaster ceilings or walls (to seal the surface over old flaky plaster or new plaster) and to seal wood when using Product 38 Intumescent Material for door upgrades.

Stabond is solvent free and has been designed to be readily absorbed to form a stable surface finish for application of fire retardant coatings, emulsions, varnishes and adhesives (including double-sided tape). Good for sealing prior to using Product 38 (included in door upgrade kits), Product 92 Coating System for wood, Product 105 (EP/CP paint for plasterboard) and Product 84 (Fireproof Paper)

Application:

Supplied ready to use. Can be applied by brush or spray.

Preparation of existing painted or varnished doors:

Wash the doors down with detergent water and clean off with warm, clean water. Ensure that all wax and grease has been cleaned off. An Envirograf® de-waxing fluid is available if required. Rub all the panels with coarse glass paper and be certain to dust off and remove all flaking varnish and ensure all corners are given a good key, then apply one coat of Stabond sealing liquid.

Tack free time: Approximately 10 minutes depending on surface type, temperature and humidity

Brushes / tools can be cleaned with warm water.

Precautions:

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.