



Product Number: 133

### AVG/F Acoustic & Fireproof Ventilation Grille

#### **Description:**

The AVG/F fireproof ventilation grille offers up to 60 minutes protection plus sound absorption. It consists of two parts (one for each side of the opening) and the internal cavity of both sections is filled with micro-acoustic material, with intumescent strips on the two long sides of the risk side opening to provide fire resistance properties.

This product comprises of the following materials and therefore is supported by Health & Safety Data Sheets:

- (Appendix 1) Intumescent material
- (Appendix 2) Fire Proof Sponge
- Preformed Zintec steel plate (not available)

\*The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the user's own assessment of workplace risk as required by other health and safety legislation.

HEALTH & SAFETY DATA SHEET  
**Appendix 1**  
MULTIGRAF INTUMESCENT MATERIAL

April 2015. Issue 2

---

**1. IDENTIFICATION OF THE PREPARATION AND COMPANY**

---

**PRODUCT NAME:** Multigraf Intumescent Material  
**MANUFACTURER/SUPPLIER:** Intumescent Systems Ltd  
**ADDRESS:** Envirograf House, Barfrestone, Dover, Kent, CT15 7JG  
**TELEPHONE / FAX / EMAIL:** 01304 842555 01304 842666 sales@envirograf.com  
**EMERGENCY PHONE NUMBER:** 01304 842555 (Monday to Friday 8.30 – 5.30)

---

**2. HAZARDS IDENTIFICATION**

---

Cutting through the material and surface scuffing may release small amounts of airborne fibre, clay and carbon dust which are mechanically irritant to skin, eyes and upper respiratory system.

Based on animal studies, excessive exposure to man made mineral fibre dust may cause lung damage (fibrosis) and tumours.

As with any dust, pre-existing upper respiratory symptoms and lung diseases may be aggravated.

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

**CHEMICAL CONSTITUTION**

Mineral Wool Fibre	20-70	%	by	weight
Exfoliating Graphite	20-60	%	by	weight
Organic binder (including adhesive coating)	5.0-30	%	by	weight

---

**4. FIRST AID MEASURES**

---

**SKIN:** Rinse affected areas with water and wash gently with soap. Do not use detergent.  
**EYES:** Flush eyes with large quantities of water, Have eye bath readily available in areas where eye contact may occur. Seek medical attention if irritation continues.  
**INGESTION:** Drink plenty of water. Seek medical advice.  
**INHALATION:** Remove to fresh air, drink water and clear throat and blow nose to evacuate fibre/dust. Seek medical attention.

---

**5. FIRE FIGHTING MEASURES**

---

**SUITABLE EXTINGUISHING MEDIA:** Use extinguishing agent suitable for type of surrounding combustible materials. Do not inhale products of combustion.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

Store product in original wrapping until required for use. Do not allow dust to be wind blown. Do not use compressed air to blow dust or fibres. Unwanted product should be collected & stored in sealed bags. Dust/fibre should be removed using a suitable vacuum cleaner with HEPA exhaust air filtration & disposal collection bags; used bags to be sealed before disposal. If sweeping is required the area should be damped down with water before brushing

---

---

## 7. HANDLING AND STORAGE

---

**HANDLING:** Keep dust generation to a minimum.

**STORAGE:** Store dry and cool. Keep in original wrapping until required for use.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### APPLICABLE OCCUPATIONAL EXPOSURE LIMITS:

**MAN MADE MINERAL FIBRE:** \*ME 2.0 fibres/ml & 5 mg/m; (8 hr TWA)

**FINE CARBON DUST:** \*OES 3.5 mg/m; (8 hr TWA) and 7 mg/m; (STEL)

\* (UK Health & Safety Executive - OEL EH40/98)

**RESPIRATORY PROTECTION:** Wear disposable dust respirator (e.g. 3M 8810 or equivalent).

**HAND PROTECTION:** Use of gloves is recommended.

**EYE PROTECTION:** Wear goggles or safety glasses with side shields. Do not wear contact lenses.

**SKIN PROTECTION:** Wear overalls that are loose fitting at the neck and wrists.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

**APPEARANCE:** Flexible Grey fibrous mat with black speckle

**DENSITY:** 200 - 500 kg/m;

**EXPANSION:** Rapid volumetric expansion occurs when product is heated above 100°C

**FLAMMABILITY:** Material will sustain combustion for a short period until organic binder (and SAB coating) is burnt out or resulting expansion self-extinguishes.

---

## 10. STABILITY AND REACTIVITY

---

**STABILITY / CONDITIONS TO AVOID:** Stable.

**MATERIALS TO AVOID:** Strong oxidizing agents, strong alkalis and hydrofluoric acid.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Combustion products are HRO, CO, COR and hydrocarbons.

---

## 11. TOXICOLOGICAL INFORMATION

---

The International Agency for Research on Cancer (IARC) has classified Mineral Wool Fibre as possibly carcinogenic (Group 2B).

---

## 12. ECOLOGICAL INFORMATION

---

This product will remain stable over time with the inorganic components remaining inert.

---

## 13. DISPOSAL CONSIDERATIONS

---

Waste is not classified as a hazardous waste and may be disposed of at a normal licensed industrial waste site. Local regulations should be considered. Waste should be bagged or suitably contained for disposal to prevent any dusts being wind blown during disposal.

---

---

#### 14. TRANSPORT INFORMATION

---

Not regulated for Transport. Ensure that dust is not wind blown during transportation.

---

#### 15. REGULATORY INFORMATION

---

LABELLING  
DANGER CLASSIFICATION -  
CONTAINS: -  
R PHRASES: -  
S PHRASES: -  
NATIONAL REGULATIONS: -

---

#### 16. OTHER INFORMATION

---

Further information regarding working with man made mineral fibres and measurement techniques may be obtained by referring to Guidance Note EH46 1990 and NDHS59 1998 published by the UK, Health & Safety Executive.

---

\*The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the user's own assessment of workplace risk as required by other health and safety legislation.

**HEALTH & SAFETY INFORMATION SHEET**  
**APPENDIX 2**  
**FIRE PROOF SPONGE**

Issue 2. December 2014

---

**1. IDENTIFICATION OF THE PREPARATION AND COMPANY**

---

**PRODUCT NAME:** Fire Proof Sponge  
**MANUFACTURER/SUPPLIER:** Envirograf  
**ADDRESS:** Envirograf House, Barrestone, Dover, Kent, CT15 7JG  
**TELEPHONE/FAX/EMAIL:** 01304 842555 01304 842666 sales@envirograf.com  
**EMERGENCY PHONE NUMBER:** 01304 842555 (Monday to Friday 8.30 – 5.30)

---

**2. HAZARDS IDENTIFICATION**

---

Not known to be a skin irritant  
Dust can cause eye irritation  
Dust generated from such operations as continuous grinding or buffing can great nuisance particles, this can cause irritation to the respiratory tract or even lung infection, airway obstruction and fibrosis  
The Control of Substances Hazardous to Health Regulations (COSHH), includes dust of any kind when present at a concentration in air equal to or greater than 10mg.m<sup>3</sup> 8-hour TWA of inhalable dust or 4mg.m<sup>3</sup> 8-hour TWA of respirable dust

---

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

Poly-addition products of isocyanates, polyols and water. Controlled by catalysts, stabilizers and other substances resulting in cellular polyurethane foams which are then post treated with flame retardants, particulate fillers and polymeric binding agent. Fire proof sponge as supplied does not contain any residual di-isocyanate.

---

**4. FIRST AID MEASURES**

---

**INHALATION:** No adverse effects anticipated  
**SKIN CONTACT:** Wash off any foam dust  
**EYE CONTACT:** In case of dust particle contact with eyes, rinse immediately with plenty of water until irritation subsides. If necessary seek medical advice  
**INGESTION:** Consult physician if coughing, discomfort or obstruction of air passage occurs.

---

**5. FIRE-FIGHTING MEASURES**

---

**GENERAL HAZARD:** Under extreme temperatures the sponge will decompose and emit toxic gases. In the event of a fire, evacuate premises immediately and call the Fire Brigade. Avoid inhalation of smoke and gases.  
**EXTINGUISHING MEDIA:** To suit local surroundings (e.g. water, carbon dioxide, foam, dry powder)  
**SPECIAL EXPOSURE HAZARDS:** Decomposition products released in a fire, (e.g. carbon black, carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide), should be considered toxic if inhaled

---

**6. ACCIDENTAL RELEASE MEASURES**

---

**METHODS FOR CLEANING UP:** Pick up and sweep up as for any other inert material  
**ENVIRONMENTAL:**  
**CONSIDERATIONS:** Do not allow to get into waste water or waterways

---

## 7. HANDLING AND STORAGE

---

**ADVICE ON SAFE HANDLING:** Handle in accordance with good hygiene and safety practice

**STORAGE CONDITIONS:** No special conditions required, but ideally to be stored in dry conditions

**FURTHER INFORMATION:** Keep away from sparks, naked lights, open flames, exposed electrical elements or other ignition sources. Smoking should be forbidden in areas where material is stored or processed

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

**PROTECTIVE EQUIPMENT:** Unless exposure to foam dust is anticipated, dust masks, goggles and gloves are not required

**VENTILATION:** Mechanical ventilation should be considered in operations that generate large quantities of foam dust

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

<b>Physical form:</b>	Cellular foam.	
<b>Colour:</b>	Dark Grey	
<b>Odour:</b>	Faint, characteristic	
<b>General Flammability:</b>	BS EN 13501-1	Euroclass B-s1, d1
	Fire Propagation Index	<12 BS476 pt 6
	Surface Spread of Flame	Class "1" BS476 pt 7
	Building Regs. 1991 (Fire Safety)	Class "0" BS476 pt 6 & pt 7
	Operating Temperature	-30 to 100°C
	UL94 Classification	94 V-0 UL 94
	Surface Burning Behaviour	Class A ASTM E84-95
<b>Density:</b>	>90 kg/M3 BS EN ISO 845	

---

## 10. STABILITY AND REACTIVITY

---

**STABILITY:** Stable under normal conditions of handling

---

## 11. TOXICOLOGICAL INFORMATION

---

**GENERAL INFORMATION:** No harmful effects have been reported to date

---

## 12. ECOLOGICAL INFORMATION

---

**DEGRADABILITY:** Almost inert

---

## 13. DISPOSAL CONSIDERATIONS

---

**ADVICE ON DISPOSAL:** Under EU Environmental Regulations and Directives, there are no special requirements for disposal of Fire Proof Sponge

**FURTHER INFORMATION:** Various methods are available for the recycling of uncontaminated cellular foam including crumbed or shredded or rebounded to produce reconstituted foam

---

---

#### **14. TRANSPORT INFORMATION**

---

Not regulated for transport

---

#### **15. REGULATORY INFORMATION**

---

Fire Proof Sponge is an “article” not a chemical. It is not classified as dangerous under the Chemicals (Hazard Information and Packaging for Supply) Regulations (CHIP), Classification, Labelling and Packaging of Chemical Regulations (CPL) & the UN’s Globally Harmonised System (GHS), and therefore does not require a Safety Data Sheet. It is exempt from the requirements to register under REACH. As a service to our customers, however Intumescent Systems Ltd has produced this data sheet.

---

#### **16. OTHER INFORMATION**

---

The information contained in the Health and Safety Data Sheet is provided in accordance with the requirements of the CHIP Regulations. The product should not be used for purposes other than those shown in section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier’s control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

---