

# APPLICATION DATA SHEET



**ENVIROGRAF®**

AP042-HW ENVIRO CLEAR-10-2018

Product Number: 42

HW Enviro Clear

Water-Based Top Coat

## **FEATURES**

HW Enviro Clear/White is a specially formulated, quick drying, water based protective top coating for INTERNAL smooth hardwood and softwood surfaces. It can be applied by brush, roller or spray and is available in matt, satin or gloss finish. It can be used over the top of the following products:

HW02 Clear & HW01 White  
ES/VFR Clear & ES/VFR White  
Q/VFR Clear & Q/VFR White  
ES/VFR/I Clear & ES/VFR/I White

## **HEALTH & SAFETY**

Do not inhale, avoid skin contact but is not harmful. Spillage on the skin should be removed with a suitable cleanser or soap and water. Wash hands before handling food. Wear a mask when spraying. Keep out of reach of children. Do not ingest. In case of eye contact, wash the area for five minutes with clean water and seek medical attention.

For more Health & Safety information please refer to data sheet.

## **PRODUCT SIZES**

This product is available in 500ml, 1 litre, 2.5 Litres, 5 Litres & 20 Litres

## **PREPARATION**

All surfaces should be clean, dry and free from loose particles and contamination.

## **APPLICATION & COVERAGE**

HW Enviro Clear does not need thinning. Stir well before application. The result is dependent on the condition of the surface and temperature of application. The coverage rate is 10-12m<sup>2</sup> per litre, for hardwearing areas apply 2 coats.

## **AFTER USE & STORAGE**

Clean tools and any spillages with warm water. Containers must be kept tightly closed and stored at a minimum temperature of 5°C and a maximum temperature of 35°C.

## **PROTECT FROM FROST.**

**DO NOT ALLOW CONTAINERS TO STAND ON THE FLOOR.**

The shelf life of this product is 1 year from date of manufacture

# SAFETY DATA SHEET



**ENVIROGRAF®**

HS042 HW Enviro Clear-03-2020

Product Number: 42

HW Enviro Clear Top Coat

HW Enviro Clear/White is a specially formulated, quick drying, water based protective top coating for INTERNAL smooth hardwood and softwood surfaces. It is available in matt, satin or gloss finish.

This product comprises of the following materials and therefore is supported by the following Health & Safety Data Sheets:

- (Appendix 58 ) HW Enviro Clear

\*The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the user's own assessment of workplace risk as required by other health and safety legislation.

**HEALTH & SAFETY INFORMATION SHEET**  
**APPENDIX 58**  
*HW ENVIRO CLEAR*

Issue 3, 11<sup>th</sup> March 2020

---

**1. IDENTIFICATION OF THE PREPARATION AND COMPANY**

---

PRODUCT NAME:	HW Enviro Clear
PRODUCT USE:	Coatings: Waterborne paint
MANUFACTURER/SUPPLIER:	Envirograf
ADDRESS:	Envirograf House, Barfrestone, Dover, Kent, CT15 7JG
TELEPHONE/FAX/EMAIL:	01304 842555    01304 842666    sales@envirograf.com
EMERGENCY PHONE NUMBER:	01304 842555

---

**2. HAZARDS IDENTIFICATION**

---

**Health effects:** Main hazard: EUH317



**Skin:** May cause mild irritation with repeated contact for individuals with sensitive skin.

**Eyes:** May cause irritation.

**Inhalation:** No Hazard under normal conditions of use

---

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

---

**Chemical characterization:** Water based clear top coat comprising of an aqueous dispersion of acrylic polymer.

Chemical Name	CAS No.	EC Number	%	Classification
2-methylisothiazol-3(2H)-one	2682-20-4		0.0057%	H301, H330, H314, H318, H400, H411, H317
Pyrrithionic zinc	13463-41-7		0.0057%	H272, H301, H318, H400, H410, H332
1,2-Benzisothiazol-3(2H)-one	2634-33-5		0.0057%	H330, H318, H400, H411, H302, H315, H317
5-Chloro-2-methyl-4-isothiazolin-3-one	26530-03-0		0.0057%	H317

---

**4. FIRST AID MEASURES**

---

**Skin contact:** Remove contaminated clothing and wash contaminated skin thoroughly with water. Obtain medical attention if symptoms develop.

**Eye contact:** Wash immediately with copious amounts of water. Seek medical attention if irritation persists.

**Inhalation:** Remove the casualty to fresh air. Obtain medical attention if difficulties persist.

**Ingestion:** If ingested in large amounts then seek medical attention – show the physician this data sheet.

---

**5. FIRE-FIGHTING MEASURES**

---

**Extinguishing media:** Select extinguishing agent appropriate for other materials involved.

**Extinguishing media which must not be used for safety reasons:** None known

**Special exposure hazards:** None known.

**Special protective equipment for fire-fighters:** Wear appropriate protective clothing and suitable breathing apparatus.

---

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Wear appropriate protective clothing & ensure standard good working industrial practice.

**Environmental precautions:** Prevent the material entering drains or watercourses. Advise Authorities if spillage has entered watercourse or sewer or has contaminated soil or vegetation. Dilute as much as possible with water and notify authorities immediately.

**Spillages:** Contain and absorb using earth, sand, cloth or other inert absorbent material.

---

## 7. HANDLING AND STORAGE

**Handling precautions:** Wear appropriate protective clothing. Adequate ventilation should be provided if there is risk of mist or aerosol formation.

**Storage conditions:** Store in closed containers between + 5°C and + 30°C in dry conditions. Avoid extremes of temperature. Protect from freezing. Normal ventilation is adequate.

---

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Occupational Exposure Standards:** -

**Personal protection equipment:** Adopt good safe standard industrial practices at all times.

**Respiratory protection:** Not normally required, use in case of insufficient exhaust ventilation or prolonged exposure.

**Hand protection:** Wear impermeable nitrile or rubber gloves.

**Eye protection:** Wear safety goggles.

**Skin and body protection:** Wear suitable overalls. Wash off any splashes immediately. No eating drinking or smoking in the work place. Practice good personal hygiene.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

Colour	White (dries to clear coat).
Form	Liquid.
Odour	Mild.
pH as supplied	6.8 – 7.1
Boiling point/range	~ 100°C.
Freezing point/range	~ 0°C.
Flash point	Not applicable.
Flammability (solid, gas)	Not applicable.
Autoignition temperature	Not applicable.
Explosive properties	Not applicable.
Vapour pressure	Not applicable.
Bulk density	1.05g/cm <sup>3</sup> .
Solubility:	
Water solubility	Miscible.
Partition coefficient (n-octanol/water)	Not determined.
Other data	-

---

## 10. STABILITY AND REACTIVITY

**Stability:** Stable under normal conditions.

**Materials and Conditions to avoid:** No hazardous reactions when stored and handled to prescribed instructions.

**Hazardous decomposition products:** No decomposition if stored and applied as directed. Thermal decomposition will generate oxides of carbon.

---

## 11. TOXICOLOGICAL INFORMATION

**Acute Toxicity:** -

**Reproduction toxicity:** Negative.

---

## 12. ECOLOGICAL INFORMATION

---

Do not allow product to enter soil, waterways or waste water.

Information on components: N/A

---

## 13. DISPOSAL CONSIDERATIONS

---

**Product:** Recommended disposal of this product is in accordance with local regulations at approved sites. Incineration is suitable.

**Uncleaned packaging:** Contaminated packaging should be emptied as far as possible and after cleansing may be reused. Packaging that cannot be cleaned should be disposed of as product waste.

---

## 14. TRANSPORT INFORMATION

---

<b>UN Class</b>	This product is not classified as dangerous goods under the United Nations Transport Recommendations.
<b>UN Packing group</b>	No special requirements.
<b>ADR</b>	Not regulated for transport.
<b>RID</b>	Not regulated for transport.
<b>IMDG</b>	Not regulated for transport.
<b>IATA</b>	Not regulated for transport.
<b>Further information:</b>	Dispatch by post permitted.

---

## 15. REGULATORY INFORMATION

---

### Labelling / Supply classification

#### National regulations

**Safety phrases:** S2 – Keep out of the reach of children  
S23 – Do not breathe vapour/spray.

---

## 16. OTHER INFORMATION

---

<b>Recommended use</b>	Top Coating to go over fire retardant / intumescent paints.
<b>Further information</b>	Consult technical data sheet.
<b>H-Phrase from section 2</b>	Trace components carry the following H-Phrases in their bulk form. H272 H301 H302 H314 H315 H317 H318 H330 H332 H400 H411

The information contained in the Health and Safety Data Sheet is provided in accordance with the requirements of the most recent REACH Regulations. The product should not be used for purposes other than those shown without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current EU legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications



Product Number: 42

### HW Enviro Clear Water-Based Top Coat

#### **Description:**

HW Enviro Clear is a specially formulated, quick drying, water based protective top coating for INTERNAL smooth hardwood and softwood surfaces. It can be applied by brush, roller or spray and is available in matt, satin or gloss finish. It can be used over the top of the following products:

HW02 Clear & HW01 White  
ES/VFR Clear & ES/VFR White  
Q/VFR Clear & Q/VFR White  
ES/VFR/I Clear & ES/VFR/I White

#### **Coverage:**

HW Enviro Clear does not need thinning.  
Coverage is 10 - 12m<sup>2</sup> per litre. For hardwearing areas apply 2 coats

#### **VOC Content:**

EU limit value for this product (Cat A/i): 140g/l (2010)  
This product contains 25g/l VOC

#### **Ordering references:**

HW Enviro Clear + size required (available in 1 litre, 2.5 litre and 5 litre containers)