

APPLICATION DATA SHEET



ENVIROGRAF®

AP042- HW Ultimate White-11-2018

Product Number: 42

HW Ultimate White

Description:

HW Ultimate white is a premium quality satin sheen finish for the use over HW01 that is suitable for interior and exterior use on wood. It provides a low odour, high opacity finish that is quick drying and non-yellowing.

Preparation:

Apply 1 coat of HW Ultimate White at 10-12m² per litre for internal use and apply 2 coats for external use.

Avoid the inhalation of dust, wear a suitable face mask if dry sanding. Treat knots with Knotting Solution and prime exposed wood. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood as they may contain harmful lead. For further advice contact Technical on 01304 842555

Application:

Stir well before use and apply by brush or roller. Apply liberally and evenly for a smooth finish. Two coats **must** be used for external use.

Do not apply in temperatures below 10°C or in damp conditions.

Cleaning:

Remove as much paint as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

Precautions:

- Ensure good ventilation during application and drying.
- Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with plenty of soap and water or a recognised skin cleaner.
- Keep out of the reach of children.
- Safety data sheet available for professional user on request.

Relevant Data:

Volume Solid	35%
Coverage	Approximately 12m ² per litre depending on the nature and porosity of the surface.
Film Thickness	Wet: 80 μ m, Dry: 28 μ m.
Drying Time	Touch dry in 1–2 hours. Re-coatable after 4 hours.
Thinner	Clean water.
Sizes	1 Litre**, 2.5 Litre, 5 Litre.

VOC Content:

Medium VOC content 8-24.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130g/l (2010).
This product contains max 130g/l VOC.

SAFETY DATA SHEET



ENVIROGRAF®

HS042 HW Ultimate White-11-2018

Product Number: 42

HW Ultimate White

HW Ultimate white is a premium quality satin sheen finish that is suitable for interior and exterior use on wood. It provides a low odour, high opacity finish that is quick drying and non-yellowing.

This product comprises of the following materials and therefore is supported by Health & Safety Data Sheets:

- (Appendix 65) HW Ultimate White

*The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the user's own assessment of workplace risk as required by other health and safety legislation.

HEALTH & SAFETY INFORMATION SHEET

APPENDIX 65

HW ULTIMATE WHITE TOP COAT

DATE OF ISSUE 12.09.2018

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

1.1 Product identifier

Product name : HW Ultimate White Top Coat
Product code : Not available
Other means of identification : Not available

1.2 Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications, Professional applications
Use of the substance/Mixture : Coating

1.3 Details of the supplier of the safety data sheet

Envirograf

Envirograf House, Barfrestone, Dover, Kent, CT15 7JG

Telephone/fax/email: 01304 842555 01304 842666 sales@envirograf.com

1.4 Emergency telephone number: Supplier 01304 842555 (Not 24 Hours)

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification According to Regulation (EC) No. 1272/2008 [CLP/GHS]:

Not classified

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label Elements

Signal word : No signal word

Hazard statements : No known significant effects or critical hazards

Precautionary statements

General: Keep out of reach of children. If medical advice is needed, have product container or label at hand

Prevention : Not applicable

Response : Not applicable

Storage : Not applicable

Disposal : Not applicable

P102, P101

Hazardous ingredients : Not applicable

Supplemental label elements: Contains 1,2-benzisothiazol-3(2H)-1, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500- 7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 1,2-benzothiazol-3 (2H)-one. May produce an allergic reaction.

Annex XVII- Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.: Not Applicable

Special packaging requirements

Containers to be fitted with child-resistant fastenings : Not applicable

Tactile warning of danger: Not applicable

2.3 Other hazards

Other hazards which do not result in classification: None known

3. COMPOSITION / INFORMATION ON INGREDIENTS

3.2 Mixtures :Mixture

Product/ingredient name	Identifiers	% by weight	Classification Regulation (EC) No. 1272/2008 [CLP]	Type
Propane-1,2-diol	REACH #: 01-2119456809-23 EC: 200-338-0 CAS: 57-55-6	≥1.0 – ≤5.0	Not classified	[2]

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

4. FIRST AID MEASURES

4.1 Description of first aid

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelid seek immediate medical advice.

Inhalation: Remove to fresh air, keep patient warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.

Skin Contact: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or a recognized skin cleaner. DO NOT USE SOLVENT OR THINNERS.

Ingestion: If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. DO NOT induce vomiting

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Potential acute health effects

Eye contact : No known significant effects or critical hazards

Inhalation : No known significant effects or critical hazards

Skin contact : No known significant effects or critical hazards

Ingestion : No known significant effects or critical hazards

Over-exposure signs/symptoms

Eye contact : No specific data

Inhalation : No specific data

Skin contact : No specific data

Ingestion : No specific data

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled

Specific treatments: No specific treatment.

5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media: Use an extinguishing agent suitable for the surrounding fire

Unsuitable extinguishing media: None known

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture: In a fire or if heated, a pressure increase will occur and the container may burst

Hazardous combustion products: Decomposition products may include the following materials: carbon oxides, metal oxide/oxides

5.3 Advice for firefighters

Special precautions for firefighters: Promptly isolate the scene by removing all persons from the vicinity of the incident there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for firefighters: Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for firefighters (including helmets, protective boots and gloves) conforming to European standard EN469 will provide a basic level of protection for chemical incidents

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding area. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

For emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel."

6.2 Environmental precautions: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers waterways, soil or air)

6.3 Methods and material for containment and cleaning up

Small spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other Sections : See Section 1 for emergency contact information

See Section 8 for information appropriate personal protective equipment
See Section 13 for additional waste treatment information

7. HANDLING AND STORAGE

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

7.1 Precautions for safe handling

Protective measures: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities: Storage temperature 5 to 25°C (41 to 77°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

See Section 1.2 for Identified uses

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values
Propane-1,2-diol	EH40/2005 WELs (United Kingdom, 12/2011) TWA: 10 mg/m ³ 8 hours. Form: Particulates TWA: 150 ppm 8 hours. Form: sum of vapour and particulates TWA: 474 mg/m ³ 8 hours. Form: sum of vapour and particulates

Recommended monitoring procedures: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres – Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres – Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres – General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
Propane-1,2-diol	DNEL	Long term inhalation	168 mg/m ³	Workers	Systemic
	DNEL	Long term inhalation	10 mg/m ³	Workers	Local
	DNEL	Long term inhalation	50 mg/m ³	Consumers	Systemic
	DNEL	Long term inhalation	10 mg/m ³	consumers	Local

PNECs

Product/ingredient name	Type	Compartment detail	Value	Method detail
Propane-1,2-diol	-	Fresh Water	260 mg/l	Assessment Factors
	-	Marine water	26 mg/l	Assessment Factors
	-	Sewage treatment plant	20000 mg/l	Assessment Factors
	-	Fresh water sediment	572 mg/kg dwt	Equilibrium Partitioning
	-	Marine water sediment	57.2 mg/kg dwt	Equilibrium Partitioning
	-	Soil	50 mg/kg dwt	Equilibrium Partitioning

8.2 Exposure controls

Appropriate engineering controls: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection: Safety glasses with side shields. Use eye protection according to EN 166

Skin protection

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Gloves: For prolonged or repeated handling, use the following type of gloves: Recommended: Viton®

Body protection: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and risks involved and should be approved by a specialist before handling this product.

Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Wear a respirator conforming to EN140. Filter type: organic vapour (Type A) and particulate filter P3

Environmental exposure controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance

Physical state	: Liquid
Colour	: White
Odour	: Faint odour
Odour threshold	: Not available
pH	: 8
Melting/freezing point	: May start to solidify at the following temperature: 0°C (32°F). This is

	based on data for the following ingredient: Water. Weighted average: -0.72°C (30.7°F)
Initial boiling point and boiling range	: >37.78°C
Flash point	: Closed cup: Not applicable [Product does not sustain combustion]
Evaporation rate	: 0.01 (propane-1,2diol) compared with butyl acetate
Material supports combustion	: No
Flammability (solid, gas)	: Liquid
Upper/lower flammability or explosive limits	: Not applicable
Vapour pressure	: Highest known value: 3.2 kPa (23.8mm Hg) (at 20°C) (water) Weighted Average: 3.1 kPa (23.33 mm Hg) (at 20°C)
Vapour density	: Highest known value: 2.6 (Air = 1) (propane-1,2-diol)
Relative density	: 1.22
Solubility(ies)	: Partially soluble in the following materials: cold water
Partition coefficient: n-octanol/water	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: Stable under recommended storage and handling conditions (see Section 7)
Viscosity	: Kinematic (40°C): >0.21cm ² /s
Explosive properties	: Product does not present an explosion hazard
Oxidising properties	: Product does not present an explosion hazard

9.2 Other information

No additional information.

10. STABILITY AND REACTIVITY

10.1 Reactivity: No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability: The product is stable

10.3 Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reaction will not occur

10.4 Conditions to avoid: When exposed to high temperature may produce hazardous decomposition products. Refer to protective measures listed in Sections 7 & 8

10.5 Incompatible materials: Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

10.6 Hazardous decomposition products: Decomposition products may include the following materials carbon oxides, metal oxide / oxides

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-

Conclusion/Summary : There are no data available on the mixture itself

Acute toxicity estimates

Route	ATE value
Not available	

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself

Eyes : There are no data available on the mixture itself

Respiratory : There are no data available on the mixture itself

Sensitisation

Conclusion/Summary

Skin : There are no data available on the mixture itself

Respiratory : There are no data available on the mixture itself

Mutagenicity

Conclusion/Summary : There are no data available on the mixture itself

Carcinogenicity**Conclusion/Summary** : There are no data available on the mixture itself**Reproductive toxicity****Conclusion/Summary** : There are no data available on the mixture itself**Teratogenicity****Conclusion/Summary** : There are no data available on the mixture itself**Specific target organ toxicity (single exposure)**

Not available

Specific target organ toxicity (repeated exposure)

Not available

Aspiration hazard

Not available

Information on the likely routes of exposure – Not available**Potential acute health effects****Inhalation** : No known significant effects or critical hazards.**Ingestion** : No known significant effects or critical hazards.**Skin contact** : No known significant effects or critical hazards.**Eye contact** : No known significant effects or critical hazards.**Symptoms related to the physical chemical and toxicological characteristics****Inhalation** : No specific data**Ingestion** : No specific data**Skin contact** : No specific data**Eye contact** : No specific data**Delayed and immediate effects and also chronic effects from short and long term exposure****Short term exposure****Potential immediate effects** : Not available**Potential delayed effects** : Not available**Long term exposure****Potential immediate effects** : Not available**Potential delayed effects** : Not available**Potential chronic health effects**

Not available

Conclusion/Summary : Not available**General** : No known significant effects or critical hazards.**Carcinogenicity** : No known significant effects or critical hazards.**Mutagenicity** : No known significant effects or critical hazards.**Teratogenicity** : No known significant effects or critical hazards.**Developmental effects** : No known significant effects or critical hazards.**Fertility effects** : No known significant effects or critical hazards.**Other information** : Not available

There are no data available on the mixture itself. The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended

Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Contains 1,2-benzisothiazol-3(2H)-1, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) and 1,2-benzothiazol-3 (2H)-one. May produce an allergic reaction.

12. ECOLOGICAL INFORMATION**12.1 Toxicity:****Conclusion/Summary** : There are no data available on the mixture itself**12.2 Persistence and degradability:****Conclusion/Summary** : There are no data available on the mixture itself

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Propane-1,2-diol	-0.92	-	Low

12.4 Mobility in soil

Soil/water partition Coefficient (Koc): Not available

Mobility : Not available

12.5 Results of PBT and vPvB assessment

PBT : Not applicable

vPvB : Not applicable

12.6 Other adverse effects : No known significant effects or critical hazards.

13. DISPOSAL CONSIDERATIONS

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s)

13.1 Waste treatment methods

Product

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste: Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	Waste paint and varnish other than those mentioned in 08 01 11

Packaging

Methods of disposal: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Type of packaging	European waste catalogue (EWC)
Container	15 01 02 plastic packaging
	15 01 04 metallic packaging

Special precautions: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

14. TRANSPORT INFORMATION

	ADR/RID	ADN	IMDG	IATA
14.1 UN number	Not regulated	Not regulated	Not regulated	Not regulated
14.2 proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 environmental hazards	No	No	No	No
Marine pollutant substances	Not applicable	Not applicable	Not applicable	Not applicable

Additional information

ADR/RID : None identified

ADN : None identified

IMDG : None identified

IATA : None identified

Special precautions for user: Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code: Not applicable

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV – List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed

Annex XVII – Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles: not applicable

Other EU regulations

Ozone depleting substances (1005/2009/EU) : Not listed

VOC for Read-for-Use Mixture: II A/d. Interior/exterior trim and cladding paints for wood and metal. EU limit values: 130g/l (2010) This product contains a maximum of 80g/l VOC

Seveso Directive

This product is not controlled under the Seveso Directive

15.2 Chemical Safety Assessment: No Chemical Safety Assessment has been carried out.

16. OTHER INFORMATION

Abbreviations and acronyms :

ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.1272/2008]

DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

PBT = Persistent, Bioaccumulative and Toxic

vPvB = Very Persistent and Very Bioaccumulative

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

IMDG = International Maritime Dangerous Goods

IATA = International Air Transport Association

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified	

Full text of abbreviated H Statements – not applicable

Full text of classifications [CLP/GHS] – not applicable

History

Date of Issue/date of revision 12th September 2018

Date of previous issue 18th February 2015

Prepared by – Intumescent Systems Ltd

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by us, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.



Product Number: 42

HW Ultimate White

Description:

HW Ultimate white is a premium quality satin sheen finish that is suitable for interior and exterior use on wood. It provides a low odour, high opacity finish that is quick drying and non-yellowing.

Key Properties:

- Non-yellowing.
- High opacity.
- Quick drying.
- Low odour satin finish.

Recommended Uses:

Suitable for interior and exterior use

Relevant Data:

Volume Solid	35%
Coverage	Approximately 10-12m ² per litre depending on the nature and porosity of the surface.
Film Thickness	Wet: 80 μ m, Dry: 28 μ m.
Drying Time*	Touch dry in 1–2 hours. Re-coatable after 4 hours.
Thinner	Clean water.
Sizes	1 Litre**, 2.5 Litre, 5 Litre.

VOC Content:

Medium VOC content 8-24.99%

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/d): 130g/l (2010).

This product contains max 130g/l VOC.