SAFETY DATA SHEET



HS105-EPCP P-01-2020

Product Number: 105

EP/CP/P Water Based Primer

Description:

EP/CP/P adhesion primer is a water-based clear primer to apply over existing painted or varnished surfaces before applying other coatings.

This product comprises of the following materials and therefore is supported by Health & Safety Data Sheets:

• (Appendix 53) EP/CP/P PRIMER

*The information contained in this safety data sheet is given in good faith. It is accurate to the best of our knowledge and belief and represents the most up to date information. The information given in this data sheet does not constitute or replace the user's own assessment of workplace risk as required by other health and safety legislation.

HEALTH & SAFETY INFORMATION SHEET APPENDIX 16

EP/CP/P

Issue 3 October 2018

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT NAME: EP/CP Primer MANUFACTURER/SUPPLIER: Envirograf

ADDRESS: Envirograf House, Barfrestone, Dover, Kent, CT15 7JG
TELEPHONE / FAX / EMAIL: 01304 842555 01304 842666 sales@envirograf.com

EMERGENCY PHONE NUMBER: 01304 842555 (Monday to Friday 8.30 – 5.30)

2. HAZARDS IDENTIFICATION

Hazard Symbol: EUH208 May produce allergic reaction



HEALTH EFFECTS:

SKIN: May cause slight irritation on prolonged / repeated contact.

EYES: May cause some irritation.

INHALATION: No hazard under normal conditions of use.

INGESTION: Low toxicity.

PHYSICAL/CHEMICAL EFFECTS: Not applicable.

3. COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL CHARACTERIZATION: Aqueous (emulsion) polymer system.

Chemical Name	CAS No.	EC Number	%	Classification
2-Methylisothiazol-3(2H)- one	2682-20-4		<0.0056%	H330/H318/H411/ H317
Pyrithione Zinc	13463-41-7		<0.0056%	H301/H330/H318/ H400/H410
1-2-benzisothiazol-3(2H)- one	2634-35-5		<0.0056%	H330/H318/H400/ H411/H302/H315/ H317

4. FIRST AID MEASURES

SKIN CONTACT: Remove contaminated clothing and wash contaminated skin with soap and water. **EYE CONTACT:** Wash with water for several minutes. If irritation persists seek medical advice.

INHALATION: Remove the casualty to fresh air.

INGESTION: Rinse out mouth with water and if conscious drink plenty of water. Seek medical attention.

5. FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Foam, carbon dioxide, powder, and water spray.

EXTINGUISHING MEDIA WHICH MUST NOT BE USED FOR SAFETY REASONS: None known

SPECIAL EXPOSURE HAZARDS: None known.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS: Chemical protection suit / gloves / boots and self

contained breathing apparatus

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Use personal protection equipment.

ENVIRONMENTAL PRECAUTIONS: Do not dispose of into surface water or sanitary sewer system.

METHODS FOR CLEANING UP: Scrape up excess and dispose of at an approved site

7. HANDLING AND STORAGE

HANDLING PRECAUTIONS: Not applicable.

STORAGE CONDITIONS: Store in closed containers between + 5°C and + 30°C in dry conditions. Avoid

extremes of temperature.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

CONTROL PARAMETERS: Not applicable. **ENGINEERING MEASURES:** Not applicable.

PERSONAL PROTECTION EQUIPMENT: RESPIRATORY PROTECTION: Not applicable.

HAND PROTECTION: Gloves. **EYE PROTECTION:** Goggles.

SKIN AND BODY PROTECTION: Not applicable

9. PHYSICAL AND CHEMICAL PROPERTIES

COLOUR: Milky White/Yellow FORM: Milky White/Yellow Liquid

ODOUR: Slight. pH AS SUPPLIED: 7 - 8

BOILING POINT/RANGE: Not applicable. MELTING POINT/RANGE: Not applicable. Not applicable. FLASH POINT: Not applicable. FLAMMABILITY (SOLID, GAS): Not applicable. **AUTOIGNITION TEMPERATURE: EXPLOSIVE PROPERTIES:** Not applicable. **OXIDIZING PROPERTIES:** Not applicable. Not applicable. **VAPOUR PRESSURE: BULK DENSITY:** $1.0 - 1.1 \text{ g/cm}^3$

SOLUBILITY:

WATER SOLUBILITY: Miscible.
PARTITION COEFFICIENT: Not applicable.

(n-octanol/water)
OTHER DATA

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Avoid extremes of temperature especially frost and freezing conditions.

MATERIALS TO AVOID: None, under normal conditions of use.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition if stored and applied as directed

11. TOXICOLOGICAL INFORMATION

Not applicable

12. ECOLOGICAL INFORMATION

Not applicable

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations at approved sites

14. TRANSPORT INFORMATION

UK ROAD/RAILNot applicable.None hazardous.IMDGNot applicable.None hazardous.ICAONot applicable.None hazardous.ADRNot applicable.None hazardous

15. REGULATORY INFORMATION

SUPPLY CLASSIFICATION: HAZARD SYMBOL(S):

EUH208 May produce allergic reaction



16. OTHER INFORMATION

RECOMMENDED USE: Adhesion Primer for wood - undercoat for wood paints and varnishes.

FURTHER INFORMATION: Consult technical data sheet.

H-PHRASE FROM SECTION 3: Trace amounts of biocide in the product carry the following H-Phrases in their

raw forms: H301/H330/H318/H400/H411/H302/H315/H317

The information contained in the Health and Safety Data Sheet is provided in accordance with the requirements of the most recent REACH Regulations. The product should not be used for purposes other than those shown without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information contained in the safety data sheet is based on present knowledge and current EU legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

TECHNICAL DATA SHEET



TD105-EPCP PRIMER-01-2020

Product Number: 105

EP/CP/P Water Based Primer

Description:

EP/CP/P adhesion primer is a water-based clear primer to apply over existing painted or varnished surfaces before applying other coatings.

Material Specification:

Composition of EP/CP/P: Water based polymer system with additives to improve

compatibility with various substrates.

Specific Gravity: 1.04 – 1.05

Tack Free Time: 20 – 50 Minutes depending on temperature & humidity.

Colour: Yellow Suspension – Dries Clear.

Storage: 12 Months in unopened original packaging

Ordering references:

EP/CP/P + size required. Available in 1 litre, 2.5 litre and 5 litre cans (See price list for full details)

APPLICATION DATA SHEET



AP105-EP/CP/P-11-2018

Product Number: 105

EP/CP/P PRIMER

Description:

EP/CP/P adhesion primer is a water-based clear primer to apply over existing painted surfaces before applying EP/CP particularly where there is distemper, dirt or dust.

Application & coverage:

EP/CP/P Primer can be applied by brush or roller. Coverage is 10-12m² per litre.

Note: It is important to ensure the moisture content of the wood substrate is below 17% before application.

After use & storage:

Use warm water to clean tools.