## TECHNICAL DATA SHEET



TD033-01-2020

# Product Number: 33 Firoblok® – Intumescent Toilet /Bathroom Ventilation Outlet Protection LV, LV /P, LVM100, LVML, EC

### **Description:**

Intumescent protection for both ceiling and wall ventilation outlets. Can be easily installed. Used with outlets which connect to toilet/bathroom ventilation fans.

### Use:

Available in sizes from 50mm to 600mm in diameter, for domestic and industrial applications.

The LV range is an internal liner for inside plastic and metal pipes from extractors and loo vents which will seal off in a fire preventing it from getting into the cavity and hollow walls. The LV /P is a length of grey PVC 1100D pipe with internal intumescent liner fitted. The LVM100 is a 100mm length of metal pipe with internal intumescent liner fitted, for cavity walls.

The LVML is a metal sleeve with fixing brackets and internal intumescent liner for round PVC and flexible pipes in ceilings and walls can be surface mounted or rebated The EC range is an externally fitted protection sleeve for PVC ventilation outlets. (Please see price list for full range and available sizes)

## **Material Specification:**

Multigraf Intumescent material chemical constitution:

Mineral Wool Fibre 20-70% by weight Exfoliating Graphite 20-60% by weight Organic Binder (including adhesive coating) 5-30% by weight

### **Test Data:**

**LPC TE 89597** 70 minutes Integrity 65 minutes Insulation