



Product Number: 63 Intumescent Cement Filler

Description:

A buff or pink coloured ready-mixed intumescent cement filler that sets hard, like normal cement, but it does not crack. In a fire, it will expand to five times its original volume. Ideal for applying around pipes, services, and behind door frames, especially steel door frames. It is also used as a facing top coat over Envirograf® Product 44 (PVE/A foam). Can also be used to fill cracks in ceilings and walls before Envirograf® Product 84 (S/Paper) is applied

Special features:

Low odour, solvent-free, user friendly, ready to use one-component cement with good wetting properties when applied onto prepared surfaces. Good adhesion to most substrates encountered in standard constructions. Can be over-painted if required.

Typical uses:

Pointing around pipes, services, flues, internal brickwork. Cures to give a hard cement-like finish, which will withstand temperatures above 1400°C +.

Technical data:

Composition:	Water based polymer system with inert fillers.
Specific gravity:	1.75
Tack free time:	30 minutes depending on bead thickness room temperature and humidity.
Full cure:	Approximately 24 hours, depending on bead thickness, room temperature and relative humidity.

Hazards:

Alkaline – may cause skin irritation on prolonged contact with skin. Irritating to eyes.
Silicate cement is based on a water-based polymer.

Ordering references:

REF	SIZE	COLOUR
CF	310ml	Natural (Buff)
CF	310ml	Pink
(Note: minimum order quantity of 25 X 310ml tubes required for the pink option)		
CF	1litre	Pink or Natural
(Please state colour required)		