



## Product Number: 73

## Rebated Acoustic, Draught, Smoke & Weather Seals

### Description:

A 3mm deep x 10mm wide x 2100mm long aluminium or plastic holder (black, brown, cream, grey, red, or white plastic) containing a brush seal in various sizes and colours or a black rubber seal in various sizes and patterns. The holder has a self-adhesive backing for ease of fitting. The seal holder is rebated into wooden doors or windows and adhered to the surface of metal windows using the self-adhesive backing on the base of the holder. It can be fitted to single or double doors, folding doors, sash windows, etc.

### Ordering References:

| REF    | DESCRIPTION   |
|--------|---|
| ES/AH  | Aluminium holder only - 10mm wide x 3mm thick                               |
| ES/AHS | Aluminium holder with seal – 10mm wide x 3mm thick (state seal required)    |
| ES/PH  | PVC holder only – 10mm wide x 3mm thick (state colour required)             |
| ES/PHS | PVC holder with seal – 10mm wide x 3mm thick (state colour & seal required) |

*Note: Plastic holder is available as 1050mm and 2100mm lengths in black, brown, cream, grey, red or white colours.*

|  |             |
|--|-------------|
| Brush Seal 5mm, 7mm, 10mm                | REF B +size |
| Rubber type angle blade 6mm, 9mm         | REF A +size |
| Rubber type tubular seal 6mm, 9mm        | REF T +size |
| Rubber type V blade 6mm                  | REF V +size |
| Rubber type straight blade 5mm, 7mm, 9mm | REF S +size |

|           |  <b>HOLDER</b> |  <b>SEAL A</b> |  <b>SEAL B</b> |  <b>SEAL S</b> |  <b>SEAL T</b> |  <b>SEAL V</b> |
|-----------|---|---|---|---|--|---|
| seal size |   | 6/9 mm  | 3/5/7/10mm  | 5/7/9mm   | 6/9mm  | 6mm   |
| USE FOR:  |   | SINGLE-ACTION DOORS AND CASEMENT WINDOWS  | DOORS AND WINDOWS   | SINGLE/DOUBLE DOORS WITH DOUBLE THRESHOLD   | ACOUSTIC CUSHIONING  | SINGLE-ACTION DOORS CLOSING ON DOOR STOP  |

**Important – 1-1½mm of the brush or rubber seal is held within the holder. Brush with fin is always ½mm higher than regular brush. Make allowance for this when specifying.**

### Test Details:

No Fire Integrity Testing On This Product As Not Required