



### Product Number: 93

### Stabond stabilising bonding/sealing liquid

#### **Description:**

Transparent water based bonding/sealing liquid for porous/friable surfaces such as plaster ceilings or walls (to seal the surface over old flaky plaster or new plaster) and to seal wood when using Product 38 Intumescent Material for door upgrades.

#### **Special features:**

Stabond stabilising bonding/sealing liquid is solvent free and supplied ready to use. The product has been designed to be readily absorbed to form a stable surface finish for application of fire retardant coatings, emulsions, varnishes and adhesives (including double-sided tape).

#### **Application:**

Ready to use.  
Can be applied by brush or spray.  
Brushes / tools can be cleaned with warm water.

#### **Typical uses:**

Used to prime / seal surfaces which may be absorbent, dusty or friable prior to painting / bonding.

#### **TECHNICAL DATA**

|                          |   |
|--------------------------|---|
| Composition:             | Water based polymer.  |
| Specific Gravity:        | Approximately 1.0   |
| Tack Free Time:          | Approximately 10 minutes depending on surface type, temperature and humidity. |
| Cure Time:               | Approximately one hour depending on surface type, temperature and humidity.   |
| Application Temperature: | +5 to +40°C   |
| Service Temperature:     | -20 to +80°C  |

#### **Storage**

Twelve months in unopened original packaging.  
Store between +5°C to +30°C.  
Protect from frost.