TECHNICAL DATA SHEET



TD101-10-2014

Product Number: 101

Intumescent Fire & Smoke Push-Fit Door Seals

Description:

Plastic intumescent fire and smoke seal. Simply clips in to routed groove with no need for adhesive or pins. Available in brown or white and in 2100mm lengths. Available with or without brush or rubber smoke seal.

Ordering references:

REF	USE	PROTECTION	SIZE
CIS14/P	Single or Double door (Plain)	30 minutes	10mm wide x 5mm deep
CIS14/30	Single Action door (Angled seal)	30 minutes	10mm wide x 5mm deep
CIS14/B30	Single or Double door (Brush seal)	30 minutes	10mm wide x 5mm deep
CIS14/S30	Single or Double door (Straight seal)	30 minutes	10mm wide x 5mm deep
CIS15/P	Single or Double door (Plain)	60 minutes	15mm wide x 5mm deep
CIS15/60	Single Action door (Angled Seal)	60 minutes	15mm wide x 5mm deep
CIS15/B60	Single or Double door (Brush Seal)	60 minutes	15mm wide x 5mm deep
CIS15/S60	Single or Double door (Straight Seal)	60 minutes	15mm wide x 5mm deep

For single doors, an angled seal will suit a gap size of 6mm down to 3mm

Availability of the seals:

Brush: 3mm, 5mm, 7mm and 10mm – for 12 or 15mm please check stock before ordering

Straight seal: 5mm, 7mm and 10mm

Important – 1-1½mm of the brush or rubber seal is held within the holder. Brush with fin is always ½mm higher than regular brush. Make allowance for this when specifying.