



Product Number: 148 Gas Flue Inspection Hatch

Description:

A new inspection hatch with a spring-loaded latch fastener, a hatch cover with a fire protection lining and fire/smoke seals. An insulated version is also available.

Uses:

On buildings that were built after 2000 where gas flues pass through plaster board ducting through rooms to vent on outside wall Gas and Building Regulations now require fire rated access panels in order to view the joints and the fixing of pipes.

Material specification:

- Zintec steel plate hatch surround and door.
- Internal locking device.
- Fire protection material fitted in door.
- Intumescent, smoke and gas seals fitted round perimeter of hatch.
- Sponge insulation (Acoustic insulated version)

Available sizes and ordering references:

Standard non-insulated version

REF:	WIDTH X HEIGHT mm
ISL/GFH/30/19	300 X 190
ISL/GFH/40/19	400 X 190
ISL/GFH/30/23	300 X 230
ISL/GFH/20/20	200 X 200
ISL/GFH/30/30	300 X 300

Acoustic **insulated** version

REF:	WIDTH X HEIGHT mm
ISL/IGFH/30/19	300 X 190
ISL/IGFH/40/19	400 X 190
ISL/IGFH/30/23	300 X 230
ISL/IGFH/20/20	200 X 200
ISL/IGFH/30/30	300 X 300

Note: Can be made to any size – prices quoted on requested

The unit has 1 -2 hour fire protection according to BS476 Part 22