



Product Number: 97

## Intumescent Door Stop for Fire & Smoke Protection

### Description:

A brown or white plastic door stop including intumescent fire seal and brush or rubber smoke seal, designed to upgrade normal hollow-core doors and to replace existing wooden door stops. Can be fitted with acoustic seals which also serve as draught and smoke seals.







### Ordering References:

| REF | DESCRIPTION |
|-----|-------------|
|-----|-------------|

|       |   |
|-------|---|
| DSU/S | Single door set consisting of 2 x 2100mm pieces and 1 x 1050mm piece  |
| DSU/D | Double door set consisting of 3 x 2100mm pieces and 1 x ES25/HS piece |

State colour and smoke seal required (see below)

|  |             |
|--|-------------|
| Brush Seal 5mm, 7mm, 10mm                | REF B +size |
| Rubber type angle blade 6mm, 9mm         | REF A +size |
| Rubber type tubular seal 6mm, 9mm        | REF T +size |
| Rubber type V blade 6mm                  | REF V +size |
| Rubber type straight blade 5mm, 7mm, 9mm | REF S +size |

|           |  <b>HOLDER</b> |  <b>SEAL A</b> |  <b>SEAL B</b> |  <b>SEAL S</b> |  <b>SEAL T</b> |  <b>SEAL V</b> |
|-----------|---|---|---|---|--|---|
| seal size |   | 6/9 mm  | 3/5/7/10mm  | 5/7/9mm   | 6/9mm  | 6mm   |
| USE FOR:  |   | SINGLE-ACTION DOORS AND CASEMENT WINDOWS  | DOORS AND WINDOWS   | SINGLE/DOUBLE DOORS WITH DOUBLE THRESHOLD   | ACOUSTIC CUSHIONING  | SINGLE-ACTION DOORS CLOSING ON DOOR STOP  |

**Important – 1-1½mm of the brush or rubber seal is held within the holder. Brush with fin is always ½mm higher than regular brush. Make allowance for this when specifying.**