



180 DEGREE ERV AWNING

Awning Setup/ Fold Away Instructions

Thank you for your purchase of the Australian made and designed **180 DEGREE ERV AWNING**.

Please follow these few simple step by step instructions to make setting up your **180 DEGREE ERV AWNING** simple to use and to improve the life span of the product

*****Please note: two people are required to set up and pack in winds over 5 knots or for unexpected wind gusts or use the supplied straps for assistance*****

Contents

- Mounting Bracket Set (2 Brackets) – Refer to installation guide
- 8 x 225mm Galv Tent Pegs
- Peg Bag
- 4 x Quick Release straps

180 DEGREE ERV AWNING

180 DEGREE ERV AWNING: Setup

1. Park at the proposed site you wish to setup, make sure you have enough clearance on the side and rear of the vehicle for the awning to fold out and expand

2. The Site should be level or close to it. If on a slight slope, face the awning down the slope as to prevent any wind getting under the awning causing it to lift

3. Remove the supplied straps & pegs from either the vehicle or awning bag



4. At the front of the vehicle, either tie one of the straps to the front bullbar / nudge bar or peg down just in front of the vehicle.

5. Tie the one of the other straps to the driver's side front roof rack and bring to the back of the vehicle (or the strap can be pegged down at the rear of the vehicle)



*****PLEASE NOTE*****

For winds over 5 knots a second person maybe required to assist for the following steps, if the tie down straps are not used

6. Roughly pace out and peg down each of the straps to line up where the awning arms (roughly 2m out from the vehicle at each end of the awning).

Unzip the tonneau bag and fold the bag over the awning



7. Undo all Velcro straps holding the canvas and aluminium extrusion.

8. Roll the canvas and front extrusion bar out and fold down the attached legs.

Hook the tie down strap to the eyelet on each end and tighten slightly (to support the awning while proceeding to the next step)



9. Once the Side section is out, each wing arm can now be swung out

Un clip the arm from the support clip and swing the arm out (you may need to drop the arm slightly to clear the upright leg) to be inline with the awning extrusion, fold down the support leg and attach the quick release strap and tighten to keep the arm inline with the awning extrusion.

Repeat these steps for the other side.



10. Once both wing arms are in position, now swing out the centre arms to support the roof section

Locate the spigot pin into the hole of the front bar extrusion, extend tight and lock the pole off

Repeat for the other side



11. Now go along and straighten up the upright poles to your desired height, tighten up the outer tie down straps

12. Peg down the folding foot plates using the wire tent pegs, cross peg the feet down to give superior holding power.

Once the feet have been pegged down, the straps holding the front bar are not required.



180 DEGREE ERV AWNING: Packing Away

*****PLEASE NOTE*****

For winds over 5 knots a second person maybe required to assist for the following steps, if the tie down straps are not used

- | |
|--|
| 1. For easy of packing away with one person, it is advised to put the quick release straps back onto the front extrusion bar to help support the awning during the packdown procedure |
| 2. In reverse order repeat steps from 12 -8

When folding the outer wing arms in, you must lift the canvas up to ensure the aluminium arm is under the canvas to allow it to clip to the aluminium extrusion |
| 3. Roll up the awning with the front bar and arms attached, use the velcro straps to hold the canvas in position while rolling up other section of canvas |
| 4. Roll up the canvas as tightly as possible and tie off with the remaining Velcro straps |
| 5. Fold over the tonneau bag and zip it up, including poles pegs and straps |

And you're done! Don't forget to clean up your site of any rubbish or debris to help keep this country beautiful.

If the awning is packed up damp. Be sure to put up again and soon as there is dry weather to dry the canvas out. Any abuse or neglect of awning can result in voiding the Warranty.

Enjoy your **180 DEGREE ERV AWNING**, any problems regarding this product please contact your local reseller or email us at info@supapeg.com.au

Check out our Supa Peg Youtube channel for more information on setup tips
<https://www.youtube.com/channel/UC2ZOHKkXi7gtTj8T9zbcMzQ>

Made by **SUPA-PEG** Australia, 100% Australian made and owned.