


RadioLINK Alarm Control Switch – Ei411H




- Install as part of the system to get more control over your Alarms
- Battery powered for life by a sealed lithium battery
- 10 year life
- Completely wire free installation
- Uses  RadioLINK™ wireless technology to interconnect to the rest of the Alarm System
- Up to 12 Alarms and Devices can be interconnected
- LED indicator for a visual display of Fire Alarm activation
- Three buttons:
 - TEST - Test alarms
 - LOCATE - Identify triggered alarms
 - SILENCE - Silence alarms
- Remote control of Alarm system from a convenient location
- Compatible with RadioLINK enabled Alarms and Devices
- For use with fire only systems

CONTAINS:



PRODUCT DESCRIPTION

The Ei411H Remote Control switch is designed for use with  RadioLINK™ enabled smoke/ heat alarms and devices. It is used to control all the alarms in a system from one convenient place. We highly recommend fitting a control switch if you have multiple smoke and heat alarms on the same system.

The Alarm Control switch increases the flexibility and user friendliness of the alarms by allowing the user to remotely Test, Locate and Silence alarms in the system.

The Test switch allows the user to test the alarms easily, without having to access the alarms on the ceiling. By pressing the Test switch all alarms will sound for a short period.

The Locate switch allows the user to identify which alarm has triggered the system to sound. By pressing the Locate switch all alarms will sound except the alarm which triggered the alarm.

The Silence switch allows the user to silence all alarms in a system if a false/nuisance alarm has been identified. By pressing the Silence switch all alarms will stop alarming for a 10 minute period.

The Ei411H is powered by a tamper proof, sealed in lithium battery enabling a completely wire free installation. The lithium battery has a 10 year life and is designed to last the life of the product. A battery on/off switch is located on the rear of the front panel to ensure battery life is maximised during shipping and storage.

The Ei411H is supplied with its own surface mount pattress and fixings.

TECHNICAL SPECIFICATION

- Power Supply:** 3V lithium battery
- Battery life:** >10 Years (normal operating conditions)
- Temperature:** Operating - 0°C to 40°C
Storage - 0°C to 35°C (in a dry area)
- Humidity range:** 15% to 95% Relative Humidity
- Button functions:** Test - Test Alarms
Locate- Identify triggered alarms
Silence- Silence alarm
- Indicator LED's:** **Red** next to Fire - Fire detected
Red - RF transmitting/ End of life
- Communication:** RadioLINK protocol
- RF frequency:** 868.499 MHZ
- Fixing:** Wall mounting - fixtures supplied
- Dimensions:** Product - 88mm x 88mm x 42mm
Package - 90mm x 90mm x 50mm
- Weight:** 216g (Boxed 195g)
- Warranty:** 5 year (limited) warranty
- Approvals:** (RF) EN 300 220-3
(EMC) EMC 301 489-3

CE 0889

Specifications are subject to change

Rev0 08/2016 LJD