



printhead cleaner built in your ribbon.

- Built right into your thermal transfer ribbons
- Preventative maintenance
- Fast and easy to use
- Maintains excellent print quality
- Prolongs printhead life
- Minimizes costly downtime



Premium Wax+



Resin Enhanced Wax

Capable and Cost Effective

Benefits


- Deep, dark bar codes, text and graphics
- Easy to use, no printer adjustment needed
- Unbeatable performance at high speeds
- Prints on a wide range of stocks
- Good durability
- Anti-static - ideal for RFID
- Guardian2 backcoat extends printhead life

Recommended Stock

Coated and uncoated paper tag and label stocks
 Polyethylene films (i.e. Polyart)
 Polypropylene films (i.e. Kimdura)

Technical Specifications

Color Code Tab.....	Clear
Print Speed.....	12 IPS
Film Thickness.....	4.5 Microns
Total Ribbon Thickness...	8.6 Microns
Transmission Density	2.7
	MacBeth
	Scale
Ink Melting Point.....	65°C/149°F



What you need to know to quote ribbon business.



Accurate Imaging Resources
 Toll Free: 800.700.7377
 Phone: 949.888.3880

Thermal Transfer Ribbon Storage Conditions

For optimal print results, thermal transfer printing should occur in the temperature range of 41° F to 95° F at 45% to 85% relative humidity. Suggested storage conditions for up to one year duration are 23° F to 104° F at 20% to 85% relative humidity. Exposing thermal transfer ribbons to direct sunlight or moisture will cause damage to the ribbons.