WTF SERIES | DEMAND REGENERATION CABINET WATER SOFTENERS





Shown without cover

BENEFITS

- Smaller amounts of soaps and detergents are needed
- Cleaner and brighter laundry
- Reduced staining, spotting and scaling
- Extended water heater life expectancy
- Prevents scale build-up in pipes, fixtures, and appliances
- Space saving unit!



WTF SERIES | DEMAND REGENERATION CABINET WATER SOFTENERS



WTF250CDR-V WTF320CDR-V

FEATURES

- Pre-loaded with C-800 high capacity resin
- Resin tank and brine tank both enclosed in a space saving cabinet
- Fleck 5600 Meter Valve
- High flow bypass valve included
- Safety float in brine tank
- Warranty Fiberglass Tank: 10 years Brine Tank Shell: 5 years Control Valve & Timer/Motor: 3 years

HARDNESS TABLE					
Less than 1.0 gpg	Soft				
1.0 - 3.5 gpg	Slightly Hard				
3.5 - 7.0 gpg	Moderately Hard				
7.0 - 10.5 gpg	Hard				
10.5 gpg and over	Extremely Hard				
	*				

Recommended range: 0 - 3.5 gpg

Hardness can leave deposits on dishes and clothing, scale in water heaters and soap in sinks and bathtubs. Clothes can look gray/unclean, and hair and skin can become dry.

MEDIA (Included)

C-800 Resin






Coarse Solar Salt

Pellet Salt

BRINE TANK MEDIA OPTIONS (Sold Separately)



Potassium Chloride









VORTECH PLATE



Environmentally friendly, reduces backwash requirement by up to 30%.

Designed for over 6,500 lbs. load capacity.

Highly efficient softening regeneration reduces annual salt consumption.

FLECK 5600 VALVE



Demand regeneration, simple to

adjust and easy to service with quick access to all internal components.

Stainless steel bypass valve.

Regenerates only as necessary, saving water and salt.

SPECIFICATIONS

Model	Capacity Grains	Unit Size HxWxD	Service Flow Rate	Backwash Flow Rate	Gal. Per Backwash	Pipe Size In/Out	50 lb bags of Salt needed	Salt used per Renegeration
WTF250CDR-V	25,000	44" x 13.5" x 22.5"	6 gpm	2.0 gpm	82	1″	5 bags	11.7 lbs
WTF320CDR-V	32,000	44″ x 13.5″ x 22.5″	8 gpm	2.0 gpm	82	1″	5 bags	15.0 lbs

