WTF SERIES | TIME CLOCK CABINET WATER SOFTENERS



BENEFITS

- Smaller amounts of soaps and detergents are needed
- Cleaner and brighter laundry
- · Reduced staining, spotting and scaling
- · Extended water heater life expectancy
- Prevents scale build-up in pipes, fixtures, and appliances
- · Space saving unit!



Shown without cover



WTF SERIES | TIME CLOCK CABINET WATER SOFTENERS



WTF250C-V WTF320C-V

FEATURES

- Pre-loaded with C-800 high capacity resin
- Resin tank and brine tank both enclosed in a space saving cabinet
- 12 Day Fleck 5600 Valve
- · High flow bypass valve included
- Safety float in brine tank

Warranty

Fiberglass Tank: 10 years Brine Tank Shell: 5 years

Control Valve & Timer/Motor: 3 years

HARDNESS TABLE					
Less than 1.0 gpg	Soft				
1.0 - 3.5 gpg	Slightly Hard				
3.5 - 7.0 gpg	Moderately Hard				
7.0 - 10.5 gpg	Hard				
10.5 gpg and over	Extremely Hard				

Recommended range: 0 - 3.5 gpg

Hardness can leave deposits on dishes and clothing, scale in water heaters and soap in sinks and bathtubs. Clothes can look gray/unclean, and hair and skin can become dry.

MEDIA (Included)

BRINE TANK MEDIA OPTIONS (Sold Separately)

C-800 Resin



Coarse Solar Salt



Pellet Salt



Iron Fighting Salt



Potassium Chloride



VORTECH PLATE



Environmentally friendly, reduces backwash requirement by up to 30%.

Designed for over 6,500 lbs. load capacity.

Highly efficient softening regeneration reduces annual salt consumption.

FLECK 5600 VALVE



1-12 day time clock valve, simple to adjust and easy to service with quick access to all internal components.

Stainless steel bypass valve.

Regenerates at pre-set intervals.

SPECIFICATIONS

Model	Capacity Grains	Unit Size HxWxD	Service Flow Rate	Backwash Flow Rate	Gal. Per Backwash	Pipe Size In/Out	50 lb bags of Salt needed	Salt used per Renegeration
WTF250C-V	25,000	44" x 13.5" x 22.5"	6 gpm	2.0 gpm	82	1"	5 bags	11.7 lbs
WTF320C-V	32,000	44" x 13.5" x 22.5"	8 gpm	2.0 gpm	82	1"	5 bags	15.0 lbs

