

WTF SERIES | DEMAND REGENERATION WATER SOFTENERS




BENEFITS

- *Smaller amounts of soaps and detergents are needed*
- *Cleaner and brighter laundry*
- *Reduced staining, spotting and scaling*
- *Extended water heater life expectancy*
- *Prevents scale build-up in pipes, fixtures, and appliances*



WTF SERIES | DEMAND REGENERATION WATER SOFTENERS



WTF240DR
WTF320DR-V
WTF480DR-V
WTF640DR-V



FEATURES

- Pre-loaded with C-800 high capacity resin
 - Fiberglass tank will not rust
 - High capacity polyethylene brine tank
 - Fleck 5600 Meter Valve
 - High flow bypass valve included
 - Safety float in brine tank
 - Warranty
- Fiberglass Tank: 10 years
 Brine Tank Shell: 5 years
 Control Valve & Timer/Motor: 3 years

HARDNESS TABLE	
Less than 1.0 gpg	Soft
1.0 - 3.5 gpg	Slightly Hard
3.5 - 7.0 gpg	Moderately Hard
7.0 - 10.5 gpg	Hard
10.5 gpg and over	Extremely Hard
Recommended range: 0 - 3.5 gpg Hardness can leave deposits on dishes and clothing, scale in water heaters and soap in sinks and bathtubs. Clothes can look gray/unclean, and hair and skin can become dry.	

MEDIA (Included)

C-800 Resin



BRINE TANK MEDIA OPTIONS (Sold separately)

Coarse Solar Salt



Pellet Salt



Iron Fighting Salt



Potassium Chloride



VORTECH PLATE



Environmentally friendly, reduces backwash requirement by up to 30%.

Designed for over 6,500 lbs. load capacity.

Highly efficient softening regeneration reduces annual salt consumption.

FLECK 5600 VALVE



Demand regeneration, simple to adjust and easy to service with quick access to all internal components.

Stainless steel bypass valve.

Regenerates only as necessary, saving water and salt.

SPECIFICATIONS

Model	Capacity Grains	Tank Size Inches	Service Flow Rate	Backwash Flow Rate	Gal. Per Backwash	Pipe Size In/Out	Brine Tank Size	50 lb bags of Salt needed	Salt used per Regeneration
WTF240DR	24,000	8" x 44"	6 gpm	1.5 gpm	67	3/4"	18" x 33"	6 bags	12.0 lbs
WTF320DR-V	32,000	10" x 40"	8 gpm	2.0 gpm	82	1"	18" x 33"	6 bags	15.0 lbs
WTF480DR-V	48,000	10" x 54"	10 gpm	2.4 gpm	94	1"	18" x 33"	6 bags	23.0 lbs
WTF640DR-V	64,000	12" x 48"	12 gpm	3.5 gpm	142	1"	18" x 40"	8 bags	30.0 lbs