


WTF SERIES | DEMAND REGENERATION TWIN TANK WATER SOFTENERS




BENEFITS

- *Smaller amounts of soaps and detergents are needed*
- *Cleaner and brighter laundry*
- *Reduced staining, spotting and scaling*
- *Extended water heater life expectancy*
- *Prevents scale build-up in pipes, fixtures, and appliances*
- *Regenerate one tank while the other is in service!*



WTF SERIES | DEMAND REGENERATION TWIN TANK WATER SOFTENERS



WTF320TTDR9100-V

WTF480TTDR9100-V

WTF640TTDR9100-V



FEATURES

- Pre-loaded with C-800 high capacity resin
- Fiberglass tank will not rust
- High capacity polyethylene brine tank
- Fleck 9100 Meter Control Valve
- High flow bypass valve included
- Safety float in brine tank
- Warranty
Fiberglass Tank: 10 years
Brine Tank Shell: 5 years
Control Valve & Timer/Motor: 3 years

HARDNESS TABLE

Less than 1.0 gpg	Soft
1.0 - 3.5 gpg	Slightly Hard
3.5 - 7.0 gpg	Moderately Hard
7.0 - 10.5 gpg	Hard
10.5 gpg and over	Extremely Hard

Recommended range: 0 - 3.5 gpg

Hardness can leave deposits on dishes and clothing, scale in water heaters and soap in sinks and bathtubs. Clothes can look gray/unclean, and hair and skin can become dry.

MEDIA (Included)

C-800 Resin



BRINE TANK MEDIA OPTIONS (Sold Separately)

Coarse Solar Salt



Pellet Salt




Iron Fighting Salt



Potassium Chloride



VORTECH PLATE



Environmentally friendly, reduces backwash requirement by up to 30%.

Designed for over 6,500 lbs. load capacity.

Highly efficient softening regeneration reduces annual salt consumption.

FLECK 9100 VALVE



Demand regeneration, simple to adjust and easy to service with quick access to all internal components.

Stainless steel bypass valve.

Regenerates only as necessary, saving water and salt.

SPECIFICATIONS

Model	Capacity Grains	Tank Size Inches	Service Flow Rate	Backwash Flow Rate	Gal. Per Backwash	Pipe Size In/Out	Brine Tank Size	50 lb bags of Salt needed	Salt used per Regeneration
WTF320TTDR9100-V	32,000	10" x 40"	8 gpm	2.0 gpm	51	1"	18" x 33"	6 bags	15.0 lbs
WTF480TTDR9100-V	48,000	10" x 54"	10 gpm	2.0 gpm	51	1"	18" x 33"	6 bags	23.0 lbs
WTF640TTDR9100-V	64,000	12" x 48"	12 gpm	3.5 gpm	95	1"	18" x 40"	8 bags	30.0 lbs