

M82738 FAQs

We are weather enthusiasts like you and know proper running equipment is important. These FAQs provide valuable information on setup, positioning, and troubleshooting your station. We recommend Adobe Reader version 10 or greater available at: <http://get.adobe.com/reader>

CONTENTS

M82738 FAQs	1
Contents	1
GENERAL INFORMATION	2
BATTERIES: What do I need to know about batteries?	2
Can I operate My station on battery power only?	2
BATTERIES: What do the battery icons mean?	2
Sensor and Station	2
What are the power requirements?	2
Will these station work in other countries?	2
SETUP: How do I setup my station?	3
MOUNTING: Where do I position my sensor & station?	3
Position Stations	3
What is Distance I Resistance I Interference?	3
How do I view my HI and LO Temperature/Humidity Readings?	4
How do I reset the Temperature/Humidity Readings?	4
TIME: Do these stations have Atomic Time?	5
How do I manually set the time?	5
BACKLIGHT: Does this station have a backlight?	6
WHAT IS Auto Dim backlight?	6
WEEKDAY: How do I correct the day of the week?	7
Does this station have 12 hour and 24 hour time options?	7
TROUBLESHOOTING	7
How do I change batteries in my sensors without losing data?	7
FACTORY RESET: How do I factory reset my station?	7
DASHES TEMP/HUMIDITY: Why does my thermo-hygro sensor show dashes on the station?	8
Why don't my temperature/humidity readings report?	8
TEMP ACCURACY: Why does my thermo-hygro sensor read inaccurately?	8
What does a reading of "HI" or "LO" mean?	8

Temperature INTERMITTANT: Why does my temp/humidity reading come and go?	9
Why am I going through batteries quickly?.....	9
How do I change between Fahrenheit and Celsius?	9

GENERAL INFORMATION

BATTERIES: WHAT DO I NEED TO KNOW ABOUT BATTERIES?

- Good fresh batteries are important for best performance in your sensors and as backup in your station.
- Batteries with an expiration date of 2025, were manufactured in 2015.
- We recommend batteries with an expiration date no more than 6 years in advance of the current year for best performance.
- A minimum voltage of 1.48 v per battery is required for best performance.
- Lithium batteries may be used in outdoor sensors. Alkaline batteries for the station.

CAN I OPERATE MY STATION ON BATTERY POWER ONLY?

- No, the power cord is required for your color station to work. Batteries are for backup.
- The Mini Display operates on batteries only.

BATTERIES: WHAT DO THE BATTERY ICONS MEAN?

- When Battery Indicator shows in the outdoor area, replace batteries in your Outdoor Sensor.
- When Battery Indicator shows next to your Time or the Indoor area, replace batteries in your Station.

SENSOR AND STATION

Your M82738 (308-1415TH & 308-1409TH) stations comes with:

TX141TH-Bv2 Thermo-hygro sensor 433MHz RF

Transmission Range 330 feet (100 meters) open air.

WHAT ARE THE POWER REQUIREMENTS?

TX141TH-Bv2: 2-AA batteries

308-1415TH: 5 volt power cord (required) and 2-AA batteries for optional backup of your time and date. Power cord is required.

308-1409TH: 2-AAA batteries

WILL THESE STATION WORK IN OTHER COUNTRIES?

- No. The color station will only work on 120 volt systems.

SETUP: HOW DO I SETUP MY STATION?

1. Insert 2-AA batteries into your Outdoor Sensor.
2. Insert the 5 volt power cord into an outlet, then into your Color Display. Optional: Insert 2-AA batteries for backup.
3. Insert 2-AAA batteries into your Mini Display.
4. Adjust time and date settings on each display.
5. Once the Outdoor Sensor is reading to each of your displays, place it outside in a shaded location.

MOUNTING: WHERE DO I POSITION MY SENSOR & STATION?

- Watch sensor mounting video: http://bit.ly/TH_SensorMounting
- Place your thermo-hygro sensor at least 6 feet off the ground.
- For accurate temperature readings your sensor needs to be shaded from the sun and in a well ventilated area. Trapped moisture will cause inaccurate readings.
- Mount your sensor vertically to allow moisture to drain out the bottom.
- Preferred location is on a north facing wall under an eave or deck rail.
- Avoid placing near a metal roof that will cause it to read high on sunny days.
- Avoid other sources of heat such as soffit vents, and window or door frames.
- For accurate humidity readings, avoid placement near vegetation and lakes or other bodies of water when possible.
- Maximum transmission distance from your thermos-hygro sensor to your station, in open air is 330 feet (100 meters).
- Insert the mounting screw through the front of the transmitter and into the wall. Tighten the screw to snug (do not over tighten).

POSITION STATIONS

Your stations are designed for placement on a desk or countertop.

- Position within reach of an outlet that is always active. Some outlets in living rooms and in bedrooms may only be active when the light switch is on.
- This color station must operate with the 5 volt power cord in order to receive sensor updates. Operation on battery power will only maintain time/date settings if you need to move your station.
- Best reception occurs when only one wall is between your station and your sensor outside.
- Position you station six feet from other electronics and wireless devices. If you suspect RF (radio frequency) interference, simply move your weather station a few feet.

WHAT IS DISTANCE | RESISTANCE | INTERFERENCE?

Distance:

- The maximum transmitting range in open air is over 330 feet (100 meters) between your sensor and your station.
- Consider the signal path from your station to your sensor as a straight line.
- Consider the distance the station is from other electronics in the home.

Resistance:

- Each obstacle: walls, windows, vegetation, stucco, concrete, and large metal objects will reduce the effective signal range by about one-half.
- Mounting your sensors on a metal fence can significantly reduce the effective signal range.

Interference:

- Consider electronics in the signal path between your sensor and your station.
- Simple relocation of your sensor or the station may correct an interference issue.
- Windows can reflect the radio signal.
- Metal will absorb the RF (radio frequency) signal.
- Stucco held to the wall by a metal mesh will cause interference.
- Transmitting antennas from: ham radios, emergency dispatch centers, airports, military bases, etc. may cause interference.
- Electrical wires, utilities, cables, etc. may create interference if too close.

HOW DO I VIEW MY HI AND LO TEMPERATURE/HUMIDITY READINGS?

The high and low temperature and humidity readings are recorded with time and date of occurrence. Each time a new high or low reading is recorded, that reading with time and date of occurrence will show.

Color Station:

To view your HI | LO records, simply press and release the PLUS (+) button.

- Outdoor HI Temperature
- Outdoor LO Temperature
- Outdoor HI Humidity
- Outdoor LO Humidity
- Indoor HI Temperature
- Indoor LO Temperature
- Indoor HI Humidity
- Indoor LO Humidity

Mini Display: NONE

HOW DO I RESET THE TEMPERATURE/HUMIDITY READINGS?

Color Station

Your temperature and humidity readings are reset individually.

1. Press and release the PLUS (+) button to view the reading you wish to reset.
2. Hold the MINUS (-) button for 5 seconds to reset individual temperature or humidity value to current temperature, humidity, time and date.
3. Press and release the LIGHT button to exit.

TIME: DO THESE STATIONS HAVE ATOMIC TIME?

- No. The time needs to be set manually on each station.

HOW DO I MANUALLY SET THE TIME?

Color Station

1. Hold the SET button for 3 seconds to enter settings menu.
2. Press and release the + or - buttons to adjust the flashing values. Hold to adjust quickly.
3. Press and release the SET button to confirm and move to the next item.

Note: Press and release the LIGHT button any time to exit settings

Settings order:

- Language (English, Spanish, French)
- Beep ON/OFF
- 12/24 Time
- Hour
- Minutes
- Year
- Month
- Date
- Temperature Fahrenheit/Celsius

Full Program Menu:

1. Hold the SET button for 2 seconds to enter setting mode. **ENGLISH** will flash. Press the + or - button to select **ESPANOL**, or **FRANCAIS**.
Note: When Español or Francais are selected, the reset of the menu items will be in that language.
2. Press SET to confirm and move to beep sound. **BEEP ON** will show. ON flashes. Press the + or - button to turn the button beep sound off.
3. Press SET to confirm and move to 12/24 hour time format. **12Hr FORMAT** will show. 12HR flashes. Press the + or - button to turn select 24 hour time format. Press SET to confirm and move to the hour. **HOUR** will show. The hour flashes. Press the + or - button to choose the hour.
4. Press SET to confirm and move to the minutes. The **MINUTES** will show. Minutes flash. Press the + or - button to choose the minutes.
5. Press SET to confirm and move to the year. The **YEAR 2018** will show. Year will flash. Press the + or - button to change the year.
6. Press SET to confirm and move to the month. The **MONTH** will flash. Press the + or - button to change the month.
7. Press SET to confirm and move to the date. **DATE** will flash. Press the + or - button to change the date.
8. Press SET to confirm and move to the temperature unit. **TEMP °F** will show. F will flash. Press the + or - button if you prefer °C (Celsius).
9. Press SET to confirm and exit.

Note: After 10 seconds with no button press, your station returns to normal time display.

Mini Display:

1. Hold the SET/IN-OUT button to enter the Settings Menu.
2. Press and release SET/IN-OUT button to confirm and move to next item or exit.
3. Press and release +/-SEARCH button to increase values. Hold +/-Search to adjust quickly.

Settings Menu Order:

- 12/24 Hour
- Hour
- Minutes
- Fahrenheit or Celsius

BACKLIGHT: DOES THIS STATION HAVE A BACKLIGHT?

Yes, your color station has a backlight with 5 levels of intensity (OFF, 1, 2, 3, 4). Power cord use is required for this station to receive updates from the sensors.

- Press and release the LIGHT button to adjust the backlight intensity or to turn it off.
- Intensity levels: 0% (OFF) | 1.5% | 20% | 50% | 100%

Mini Display-No backlight.

WHAT IS AUTO DIM BACKLIGHT?

Color Station:

AUTO DIM allow you to set a time for your backlight to dim to level 1 and then return to level 5. This is a handy feature to dim the backlight at the same time every night for sleep.

Set Auto Dim (Hour only).

1. Hold the LIGHT button 2 seconds to enter dimmer set mode. **AUTO DIM OFF** will show.
2. Press the + or – buttons to turn dimmer (ON). **AUTO DIM ON** will show.
3. Press the LIGHT button to select start time (Hour) for dimmer. **START TIME** and the **hour** will flash.
4. Press the + or – buttons to change the hour for the dimmer to be low light level.
5. Press the LIGHT button to select start time for dimmer to be on High light level. **STOP TIME** and the **hour** will flash.
6. Press the + or – buttons to change the hour for the dimmer to be high light level.
7. Press the LIGHT button to confirm exit.

Note: While Auto Dim is active:

- Press and release the LIGHT button to adjust the backlight for 10 seconds. Intensity Levels: OFF | 1.5% | 20% | 50% | 100%.
- If you change the backlight setting the station will stay on the new setting and will automatically go back to the auto dim on the next start point.

WEEKDAY: HOW DO I CORRECT THE DAY OF THE WEEK?

- The day of the week will set when the Year, Month, and Date are set. If your day of the week is incorrect, yet the month and date are correct, please go the [program menu](#) and check the YEAR setting.

DOES THIS STATION HAVE 12 HOUR AND 24 HOUR TIME OPTIONS?

- Yes, you can select 12 hour or 24 hour time format in the [program menu](#) of both stations.

TROUBLESHOOTING

HOW DO I CHANGE BATTERIES IN MY SENSORS WITHOUT LOSING DATA?

Color Station:

We designed this station for convenience, so that a simple change of batteries does not lose data or require you to power down your station.

- When Battery Indicator shows next to the Outdoor Humidity, replace batteries in your Outdoor Sensor.
- Then hold the PLUS (+) button for 3 seconds and your station will search for your sensor.
- When changing the batteries in the color station, continue using the power cord. After replacing the batteries, no other action is needed. The batteries in the station only maintain time/date in the event of a power outage.

Mini Display:

Hold the +/-SEARCH button to search for the outdoor sensor.

FACTORY RESET: HOW DO I FACTORY RESET MY STATION?

- Basically this is a great way to return your station to “out of the box” condition.
- This is more effective than removing all power for clearing out the station.
- All history records will be removed, so write down anything you want to keep.

To factory either station:

1. Bring your sensor in, and place 5-10 feet from both stations.
2. Remove power (batteries and power cord) from stations and sensor for 15 minutes.
3. With power removed press any button 20 times.
4. Insert power cord and batteries into sensor and stations.
5. Allow 15 minutes for them to connect several times.
6. Place sensor back outside.

DASHES TEMP/HUMIDITY: WHY DOES MY THERMO-HYGRO SENSOR SHOW DASHES ON THE STATION?

Dashes indicate the connection is lost between your station and the outdoor sensor.

- My first thought is always to check that my [batteries](#) are good. If it has been working and now is not, low batteries are the most common connection problem.
- Next, check your [distance, resistance and interference](#). If everything was working previously at the same location, this is likely not the issue. However sometimes there is new growth on trees or bushes that causing another barrier. Radio Frequency (RF) signal does not travel well through foliage due to the moisture content.
- Occasionally adding a new wireless electronic device to the home will cross the signal path for the sensor. If this occurs try moving your station a few feet or turning the station 90 degrees for a better angle to receive the sensor signal.
- When you have good batteries, and good location, hold the PLUS (+) button (Color Station) or +/SEARCH button (Mini Display) for three seconds to search for your sensor. If you regain connection while the sensor is mounted, great. If you do not regain connection, bring the sensor within 10 feet of the station and complete a factory reset.

WHY DON'T MY TEMPERATURE/HUMIDITY READINGS ON MY STATION MATCH THE WEATHER REPORT?

- Your temperature and humidity readings are from you sensor at your location. Your local reporting station can be miles away so readings may differ.

TEMP ACCURACY: WHY DOES MY THERMO-HYGRO SENSOR READ INCCURATELY?

- The thermo-hygro sensor reads the environment. If your sensor reads high during the day but not at night it is a [mounting](#) problem.
- **Side-by-side test:** Bring the thermo-hygro sensor in the house and place it next to your station for 2 hours.
- Compare indoor and outdoor temperature. The temperatures should be within 4 degrees to be within tolerance. The humidity should be within 14% to be within tolerance.
- If the sensor reads correctly when next to your station then try a different location outside.
- Look for heat sources such as sunlight, door or window frames, or reflected heat that may cause inaccurate readings.
- If your temperature is reading low, and location is not an issue, you may have a bad sensor.

WHAT DOES A READING OF “HI” OR “LO” MEAN?

- If your outdoor temperature reading shows “HI” or “LO”, check that your [batteries](#) are good.
- Overpowered or underpowered batteries can cause this reading.

- If batteries are good, replace the outdoor sensor.
- If your temperature is fine but your humidity is reading “HI” or “LO” or dashes, your humidity may be below 10% Relative Humidity. Your sensor does not read below 10% humidity.

TEMPERATURE INTERMITTANT: WHY DOES MY TEMP/HUMIDITY READING COME AND GO?

- RF (radio frequency) communication may come and go occasionally. This can be normal in some environments (e.g. moister climates).
- If a sensor goes out, please wait 2-4 hours for it to reconnect on its own. Please be patient – these stations can reconnect on, after many hours out.
- RF (radio frequency) communication is not always 100% on. Certain temporary conditions can cause it to go out for a time (e.g. 100% humidity).

If a miss happens:

- If sensor loses connection to the station for any reason, the station will show dashes after 30 minutes.
- The station will search for 5 minutes every hour to reconnect with sensor.
- Be sure you have good [batteries](#). Manually search for your sensor by holding the PLUS (+) or +/-SEARCH button for three seconds.

Try this:

- Bring your sensor within 10 feet of your station and make sure it is connected to the station.
- After 15 minutes move the sensor into the next room with a wall between the sensor and the station for 1 hour.
- If there is no loss of signal in that hour, move the sensor just outside.
- Continue moving the sensor back to its original location.
- If you lose connection, look for sources of [interference](#).

WHY AM I GOING THROUGH BATTERIES QUICKLY?

- Test a new set of [batteries](#). Write down the date of installation and the voltage of the batteries.
- When the batteries fail, please note the date and voltage again. This is helpful in determining the problem.
- Check for leaking batteries, which may damage the sensor.

HOW DO I CHANGE BETWEEN FAHRENHEIT AND CELSIUS?

- On your station enter the [program menu](#) to select Fahrenheit or Celsius temperature display on the station.