

UNIVERSAL TREE STRAP

INSTALLATION GUIDE

PROVIDED IN BOX:







Protector



Loop Holders

TOOLS YOU WILL NEED:









Ladder

Eye Protection

Tape Measure



1 Select Tree Branch

Select a sturdy branch from a large, healthy tree at least 10 inches in diameter. Mature hardwood trees like oak are the best choices. Avoid trees with visible cracks and decayed branches.



3 Cinch and Tighten

Pull tight cinching strap snugly against branch. If multi-loop side of strap hangs lower than desired, wrap strap slack TIGHTLY around branch until it reaches desired height off ground. Then, thread multi-loop side of strap through the single loop again and cinch tight.



2 Secure Tree Protector and Drape Strap

WEARING EYE PROTECTION and using a ladder if necessary, tightly wrap and secure tree protector on branch. Then, evenly drape strap over tree protector. Thread multi-loop side of strap through single loop.



4 Test Installation

To avoid hazard, an adult should pull tight and add at least 200 lbs on strap eliminating excess slack. Your strap is now ready for swing install. Please reference your swing's installation guide. For easy connection, use carabiner provided. Secure excess loops with holders if necessary.

Technical Specifications

Length

Weight Limit:

12 feet

1000 lbs



AWARNING

Read and understand the instructions and warnings before installation and use

AWARNING

- Swinging on tree swings involves inherent risk than can cause serious injury or even death.
- Do not use the equipment until properly installed.
- This product is intended for residential use. It is NOT intended for public or commercial use.
- This product is NOT suitable for any lifting or towing application.
- It is recommended to find a tree branch with at least a 10" diameter on a healthy tree
- · Adult supervision is required.

Observing the following statements and warnings reduces the likelihood of serious or fatal injury:

- Children should be instructed to NOT walk close to, in front of, or behind the swing while in use.
- Children should be instructed to NOT swing an empty swing, as the
 potential to be struck by the empty swing exists.
- Children should be instructed to sit in the center of the swing with their full weight on the seat
- Children should be told NOT to use the swing in manners other than intended
- Children should be instructed NOT to get off the swing while it is in motion.
- Children should NOT wear neck drawstrings or other loose fitting items due to strangulation risk.
- Children should be instructed NOT to play on swing when the swing is wet.
- Children should be instructed to NOT attach items to the swing, such as, but not limited to jump ropes, kite strings, pet leashes, cables, chains as those items present a strangulation risk.
- Children should remove their bike or other sport helmet before playing on the swing.
- Children should be instructed to wear well-fitting footwear that fully encloses the foot. Flip-flops and sandals are not considered appropriate.
- Straps may tighten and stretch over time. Be sure the height of your applications is always at a safe height and not too close to the ground.
- Users should inspect strap for wear and tear and replace immediately if wear is found.



INSTALL IN A SAFE PLACE

Place your swing over level ground.

Do not install over concrete, asphalt,
packed earth or any other hard surface.

Ensure the branch is at least 10" in
diameter and the tree is healthy. Make
sure the swing is at least 6 ft away from
any structure or obstruction, such as
tree trunks, buildings and fences. Please
visit htttps://www.cpsc.gov/s3fs-public/324.pdf for future reference.

GENERAL NOTICES

- Purchaser and users assume all risk, responsibility, and liability for use of the Yardbird Universal Tree Strap, including any resulting loss or damage to persons or property.
- Yardbird Outside LLC assumes no liability arising from the use of or application of any of its products and specifically disclaims any and all consequential and incidental damages



We've got you covered.

Yardbird is dedicated to providing exceptional products that are quality tested and guaranteed against defects in materials and workmanship for 3 years after the original date of purchase.

Please save this product guide in the event you need to contact us concerning your product.

QUESTIONS? LET'S CHAT.

help@yardbirdoutside.com

14121 Highway 290 Suite 12B Austin, TX 78737

