



LCH-GS100 CUSTOMIZABLE PAINT BOOTH





Features

- All panels are 18 ga. satin coated powder coated
- All roof stiffeners are 12 ga. steel with double layers
- Twelve light fixtures 4' x 2', 110V with clear tempered glass (All lights are outside accessible)
- Exhaust fans 34" diameter, 3 Hp Motor 575 V / 3 ph, 60Hz
- Entrance door 11'H x 10'W
- One man door with view window
- Heated air make-up unit is required to supply replacement air for paint booth exhaust fans
- 80°F temperature rise in spray mode, 160°F temperature rise in bake mode
- Natural gas
- System stops automatically
- Customization





Specifications

- Overall dimension (m) 7.0 x 5.3 x 3.5
- Inner dimension (m) 6.9 x 3.9 x 2.7
- Width of door for entrance of vehicle(m) 3.0
- Height of door for entrance of vehicle(m) 2.7
- Filtrated area(m²) 20
- Air flow Volume (m²/h) 21000
- Air velocity within booth(m/s) 0.25~0.35
- Ventilation time (times/h) 265
- Working temperature (°C) 60~80
- Oil consumption (kg/set) 6~8
- Insulation material of wall panel PE
- Power (kw) 9
- Main blower: European style professional blower unit 7.5 KW











