





## **Features**

- Heavy Duty Construction
- Designed to withstand the most challenging shop environments.
- Durable welded steel frame
- Removable Tank for Transport, eliminates the need for scale locks
- Double flushing system for zero gas switching contamination
- 2 tank supply connectors included (R134a and 1234YF gas)
- Latest OE database- lifetime updates
- Additional filter included
- Dust cover included
- Dual system for R134a and 1234YF
- Services standard and hybrid vehicles
- Maintenance-free, self-diagnosis
- Comes with 3m(10ft) long hoses
- Integrated printer to produce test results.
- Automatic & manual used oil drain/oil injection
- Extensive oil and refrigerant database
- Dust cover included
- Fully automatic functions
- Gas qty usage smart monitoring

## **Included Accessories**





Additional filter



2 tank supply connectors (R134a and 1234YF gas)

## **Specifications**

- Load cell precision: +/- 10g
- Load cell precision (oil bottle): +/- 5g
- Vacuum pump capacity: 4.5CFM, 3Pa
- Service hose length: 2 sets/3m (5 ft) each
- Supply tank capacity: 12L each/ 2 separate tanks
- Display: 5" control screen
- System: Pressure purge system
- Pulse flush: Clean flush to avoid contamination
- Type of refrigerant: R134a and 1234YF
- Voltage: 110-240V/50-60Hz
- Unit dimension: (WxDxH,mm) 670x730x1445
- Weight: 100kg

