

## ELITE

### Interior Low Sheen Acrylic

Product Code: EILSW

#### Product Description

Haymes Elite Interior is a premium quality, low odour, water-based 100% acrylic paint that's 99% VOC free. It's easy to apply, washable and ideal for interior walls and exterior sheltered surfaces. It is ideal for use in areas such as kid's bedrooms, living rooms and high traffic areas where a hard wearing, scrubbable finish is required. The low sheen finish can be used for kitchens and bathrooms where high levels of moisture or steam are present. The low odour formulation ensures there are no nasty smells during and after painting.

#### Product Features

- ✓ No fumes or odours
- ✓ Superior coverage
- ✓ Easy to clean
- ✓ Scrubbable & stain resistant



#### Where to use

Interior Plasterboard, Timber, Masonry and Pre-painted surfaces.

#### Typical Properties

Gloss	Low sheen 5 -10
Colour	White, Tintable.
Sizes	4L, 10L, 15L
Clean Up	Water
Dry Time	Touch Dry 20 mins Recoat 2 hours
Coverage	Up to 16m <sup>2</sup> /L
Film Build	Wet 62um Dry 27um
Volume Solids	42%
VOC	<5g/L
Approvals	APAS 0215/3, 0260/3
Application tools	Brush, Roller, Spray

#### Surface Preparation

General Surface Preparation	<ol style="list-style-type: none"> <li>1. Fill cracks, nail holes and imperfections with Haymes Unifill.</li> <li>2. Scrape all loose/flaking paint. Sand smooth &amp; dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.</li> <li>3. Prime bare plaster, timber and metal areas with appropriate undercoats or primers.</li> </ol>
Previously Painted Surfaces	<ol style="list-style-type: none"> <li>1. Prepare any damaged areas as for General Surface Preparation.</li> <li>2. Apply one coat of Haymes Acrylic Sealer Undercoat to any patched areas.</li> <li>3. Sand gloss surfaces to a dull finish. Remove all dust</li> </ol>

Plasterboard	<ol style="list-style-type: none"> <li>1. Prepare any damaged areas as for General Surface Preparation.</li> <li>2. Apply one coat of Haymes Acrylic Sealer Undercoat.</li> </ol>
Timber	<ol style="list-style-type: none"> <li>1. Prepare any damaged areas as for General Surface Preparation.</li> <li>2. Apply one coat of Tricoat.</li> </ol>
Masonry, Brick, Concrete, Render	<ol style="list-style-type: none"> <li>1. Wash with Haymes Unikleen &amp; rinse with clean water.</li> <li>2. Apply one coat of Haymes Acrylic Sealer Undercoat.</li> </ol>

### Application

Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.

- Stir thoroughly before and during application.
- Apply 2 coats by brush, roller or spray.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.

### Thinning

Thinning is not recommended unless spraying; add up to 100ml clean water per litre of paint to achieve acceptable atomisation. Up to 50ml of water can be added per litre of paint to ease application under very warm conditions.

### Care and Maintenance

New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for 7 days. After 7 days the finish can be cleaned with a mild detergent solution and a soft cloth.

### Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

### First Aid & Safety Advice

**Keep out of reach of children.** Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

### Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

### Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint (1800 033 431). We are continually updating materials and methods, so please ensure you have the latest information.

**Please check the colour for accuracy prior to application. Haymes Paint accepts no responsibility for the application of incorrect colours.**

### Disclaimer

The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time; those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable

written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Freecall 1800 033 431  
Freefax 1800 801 892  
[www.haymepaint.com.au](http://www.haymepaint.com.au)

**Date of Preparation** 19/7/13