

## SAFETY DATA SHEET

### Section 1. Identification of the material and the supplier

Product: **Weatherfast Premium Enamel**  
 Item Code: 8000  
 Product Use: High gloss water resistant paint for severe exposure conditions. Applied by brush, roller or spray  
 Restriction of Use: Refer to Section 15

Australian Supplier: **Norglass Paints**  
 Address: 59 Moxon Road  
 Punchbowl NSW 2196  
 Australia  
 Telephone: +61 2 9708 2200  
 Email: [info@norglass.com.au](mailto:info@norglass.com.au)

New Zealand Supplier: xxx  
 Address: xxx  
 Telephone: 0508 724687

**Emergency Numbers:**  
**Australia: 13 1126 (Poisons Information Centre)**  
**New Zealand: 0800 764 766 (National Poison Centre)**

Date of SDS Preparation: 15 November 2018 v2

### Section 2. Hazards Identification

**Australia:**  
 Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

**New Zealand:**  
 This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

**EPA Approval No: Surface Coatings and Colourants (Flammable, Toxic[6.7]) – HSR002669**

#### Pictograms



Flammable    Toxic/Irritant    Chronic    Ecotoxic

Signal Word: DANGER

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Flam. Liq. 3
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1

6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.5B	H317	May cause an allergic skin reaction.	Skin Sens. 1
6.7B	H351	Suspected of causing cancer.	Carc. 2
6.8B	H361	Suspected of damaging fertility or the unborn child.	Repr. 2
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	STOT RE 2
9.1B	H411	Toxic to aquatic life with long lasting effects.	Aquatic Chronic 2

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fume, gas, mist or vapours.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.
P281	Use personal protective equipment as required.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P314	Get medical advice/attention if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P391	Collect spillage.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P303 + P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

Storage Code	Storage Statement
P405	Store locked up.
P403 + P235	Store in a well-ventilated place. Keep cool.

Disposal Code	Disposal Statement
P501	Dispose of according to Local Regulations or Authorities

### Section 3. Composition / Information on Ingredients

Ingredients	Wt%	CAS NUMBER.
Urethane Alky Resin	50 - 69	Proprietary
White Spirits	10 - 15	64742-88-7
Pigments various	5-20	Proprietary
Additives	Up to 100	Proprietary

### Section 4. First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult.

### Most important symptoms and effects, both acute and delayed

Symptoms:

**Ingestion:** Not applicable.

**Inhalation:** Not applicable.

**Skin:** Causes skin irritation. May cause an allergic skin reaction.

**Eye:** Not applicable.

**Chronic:** May be fatal if swallowed and enters airways. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

## Section 5. Fire Fighting Measures

<b>Hazard Type</b>	Flammable Liquid
<b>Hazards from combustion products</b>	Oxides of carbon, possible toxic fumes
<b>Suitable Extinguishing media</b>	Extinguishing media carbon dioxide foam or dry chemicals.
<b>Precautions for firefighters and special protective clothing</b>	Wear full protective gear.
<b>HAZCHEM CODE</b>	<b>3Y</b>

## Section 6. Accidental Release Measures

### Personal precautions:

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel.

### Environmental precautions:

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Notify authorities if product enters sewers or public waters.

### Spill and Disposal procedures:

Extinguish all sources of ignition. Spilt material should be absorbed into dry inert material such as sand, earth or sawdust and disposed by incineration by approved agent or local regulations.

## Section 7. Handling and Storage

### Precautions for Handling:

- Read label before use.
- Do not handle until all safety precautions have been read and understood.

- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust, fume, gas, mist or vapours.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Avoid release to the environment.
- Wear protective clothing.

**Precautions for Storage:**

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Keep out of reach of children.

**Section 8 Exposure Controls / Personal Protection**

**WORKPLACE EXPOSURE STANDARDS (provided for guidance only)**

Substance	TWA	STEL
	ppm mg/m <sup>3</sup>	ppm mg/m <sup>3</sup>

No ingredients have known exposure limits.

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

**Engineering Controls**

Use only in well ventilated areas. Introduce local exhaust ventilation if necessary.

**Personal Protection Equipment**



<b>Eyes</b>	Wear safety goggles.
<b>Hands and Skin</b>	Wear neoprene rubber gloves. Wear overalls and use barrier cream.
<b>Respiratory</b>	Avoid breathing vapour of dust by wearing organic vapour respirators.

**Section 9 Physical and Chemical Properties**

<b>Appearance</b>	Coloured viscous liquid
<b>Odour</b>	Low solvent
<b>Odour Threshold</b>	Not applicable
<b>pH</b>	Not applicable
<b>Boiling Point</b>	150°C for solvent
<b>Melting Point</b>	Not applicable
<b>Freezing Point</b>	Not applicable
<b>Flash Point</b>	32°C
<b>Flammability</b>	Not applicable
<b>Upper and Lower Exposure Limits</b>	Not applicable
<b>Volatile Component</b>	20-25
<b>Vapour Density</b>	Not applicable

<b>Specific Gravity</b>	0.930 – 1.180
<b>Solubilities</b>	Insoluble
<b>Partition Coefficient:</b>	Not applicable
<b>Auto-ignition Temperature</b>	Not applicable
<b>Decomposition Temperature</b>	Not applicable
<b>Kinematic Viscosity</b>	Not applicable
<b>Particle Characteristics</b>	Not applicable

### Section 10. Stability and Reactivity

<b>Stability of Substance</b>	This product is stable under normal conditions.
<b>Conditions to Avoid</b>	Sources of ignition. Heat.
<b>Incompatible Materials</b>	None known.
<b>Hazardous Decomposition Products</b>	Oxides of carbon, possible toxic fumes

### Section 11 Toxicological Information

#### Acute Effects:

<b>Swallowed</b>	Not applicable.
<b>Dermal</b>	Not applicable.
<b>Inhalation</b>	Not applicable.
<b>Eye</b>	Not applicable.
<b>Skin</b>	Causes skin irritation. May cause an allergic skin reaction.

#### Chronic Effects:

<b>Carcinogenicity</b>	Suspected of causing cancer.
<b>Reproductive Toxicity</b>	May damage fertility or the unborn child.
<b>Germ Cell Mutagenicity</b>	Not applicable.
<b>Aspiration</b>	May be fatal if swallowed and enters airways.
<b>STOT/SE</b>	Not applicable.
<b>STOT/RE</b>	Causes damage to organs through prolonged or repeated exposure.

### Section 12. Ecotoxicological Information

New Zealand:

HSNO Classes: 9.1B = Toxic to aquatic life with long lasting effects.

<b>Persistence and degradability</b>	No data available
<b>Bioaccumulation</b>	No data available
<b>Mobility in Soil</b>	No data available
<b>Other adverse effects</b>	No data available
<b>Precautions</b>	Do not allow to enter waterways.

### Section 13. Disposal Considerations

**Disposal Method:** Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from ignition sources.

**Precautions:** Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable, Ecotoxic". If triple rinsing container, add rinsate to waste container for disposal.

**Disposal methods to avoid:** Do not allow to enter waterways.

## Section 14 Transport Information

**This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).**

**This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012**



### Road and Rail Transport

UN No: 1263  
Class-primary: 3  
Packing Group: III  
Proper Shipping Name: PAINT, FLAMMABLE LIQUID

### Air Transport

UN No: 1263  
Class-primary: 3  
Packing Group: III  
Proper Shipping Name: PAINT, FLAMMABLE LIQUID

### Marine Transport

UN No: 1263  
Class-primary: 3  
Packing Group: III  
Proper Shipping Name: PAINT, FLAMMABLE LIQUID

### **Limited Quantities Statement:**

If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

## Section 15 Regulatory Information

### **Australia:**

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a **Schedule 5** Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

### **New Zealand:**

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable, Toxic [6.7]) – HSR002669

HSNO Classification: 3.1C, 6.1E(asp), 6.3A, 6.5B, 6.7B, 6.8B, 6.9B, 9.1B

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1000L(9.1B)

Emergency Response Plan	1000L(9.1B)
Secondary Containment	1000L(9.1B)
Restriction of Use	Only use for the intended purpose.

## Section 16 Other Information

### Glossary

EC <sub>50</sub>	Median effective concentration.
EEL	Environmental Exposure Limit.
EPA	Environmental Protection Authority
HSNO	Hazardous Substances and New Organisms.
HSW	Health and Safety at Work.
LC <sub>50</sub>	Lethal concentration that will kill 50% of the test organisms inhaling or ingesting it.
LD <sub>50</sub>	Lethal dose to kill 50% of test animals/organisms.
LEL	Lower explosive level.
OSHA	American Occupational Safety and Health Administration.
TEL	Tolerable Exposure Limit.
TLV	Threshold Limit Value-an exposure limit set by responsible authority.
UEL	Upper Explosive Level
WES	Workplace Exposure Limit

### References:

#### Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.
2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).
3. Standard for the Uniform Scheduling of Medicines and Poisons.
4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
6. Workplace exposure standards for airborne contaminants, Safe work Australia.
7. American Conference of Industrial Hygienists (ACGIH).
8. Globally Harmonised System of Classification and Labelling of chemicals.

#### New Zealand:

1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
4. Transport of Dangerous goods on land NZS 5433:2012
5. HSW (Hazardous Substances) Regulations 2017

### Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date: 15 November 2018 Review Date: 15 November 2023