FINE FINISH SPECIFICATIONS

FinishPro II

FF GX19

395 PC

595 PC PRO







			- 1 'm
SPECIFICATIONS			
Part numbers	17H223	17C 321	17E915
Max. tip size: 1 gun	0.019"	0.023"	0.027"
Max. flow - I/min. (gpm)	1.4 (0.38)	2.0 (0.54)	2.6 (0.68)
Max. pressure - bar (PSI)	207 (3000)	227 (3300)	227 (3300)
Motor rating - kW (HP)		0.65 (0.875) TEFC Brush DC	1.04 (1.4) Brushless DC
Turbine / compressor l/min. (cfm)		2.0 (0.47)	2.7 (0.7)
Max. air working pressure - bar (PSI)		2.4 (35)	2.4 (35)
Weight - kg (lbs)	12.3 (26)	50 (110)	51 (112)
FEATURES			
BlueLink™			
SmartControl™		1.0	3.0
Air pressure guage			
FastFlush™			
Endurance™ Pump			
ProConnect™			
SmartComp™			•
Hose Rack			
COMPOSITION			
Tips	FFLP210	FFLP210 + LTX517 + AAM309	
Flat to RAC® conversion kit			
Gun filter (mesh)	Easy Out™ 100 - 287033	100 - 224453	
Pump filter (mesh)		Easy Out™ 100 - 246382	
Gun	FTx™- 288430	G40 - 262932	
Hose	3/16" x 7.5m - 214698	Super-Flex Fluid+ Air; Hose (15M) + Whip (2M) 24U579 Hose protector 24U577	Super-Flex TM Fluid + Air; Hose (15M)+ Whip (2M) 24U579; Hose protector 24U577
Whip hose		Hose protector 24U577	Hose protector 24U577
Tools			
10015	Built-In pump removal tool	•	



