PROFESSIONAL AIRLESS SMALL ELECTRICS SPECIFICATIONS

GX 21







SPECIFICATIONS				
Part numbers	17H219	Stand 17C384 .	Stand 17C386 Lo-Boy 17C387 Hi-Boy 17C388	Stand 17E881
Max. tip size	0.021"	0.019" :	0.021"	0.023"
Max. flow - I/min (gpm)	1.8 (0.47)	1.8 (0.47)	1.8 (0.47)	2.0 (0.52)
Max. pressure - bar (PSI)	207 (3000)	207 (3000)	227 (3300)	227 (3300)
Weight - kg (lbs)	13.2 (29)	14 (30)	14 (30)	19 (41)
Motor HP		5/8 DC	5/8 DC	5/8 TEFC DC
FEATURES				
Frame	Direct Immersion			
Hopper	Suction Tube			
Ball Knocker - PushPrime™ Button	.			
Hydraulic Pressure Gauge	■ ·			
ProXChange™ Pump System	•			
Pump		Endurance Piston		
ProConnect™				
Control		Electronic		SmartControl 1.0
COMPOSITION				
Tips	51.7	RAC X LTX 515	RAC X LTX 515	RAC X LTX 517 - LP 315
Guard	RAC X™ - 246215			
Gun filter (mesh)	Easy Out™ 60 - 288749			
Gun	SG3	SG3	FTx	Contractor PC
Pump filter (mesh)	40 - 288747			
Hose	1/4" x 15m - 247340	Blue Max II Airless 6.4 mm x 15 m (1/4 in x 50 ft)		



