

SAFETY DATA SHEET

Section 1. Identification of the material and the supplier		
Product: Item Code: Product Use:	Northane Hardener 5005 Hardener for Northane Base 2 pack Polyurethane Paint (Polyester Polyurethane) for use in accordance with Product Data Sheet.	
Restriction of Use:	Refer to Section 15	
Australian Supplier: Address:	Norglass Paints 59 Moxon Road Punchbowl NSW 2196 Australia	
Telephone: Email:	+61 2 9708 2200 info@norglass.com.au	
New Zealand Supplier: Address:	XXX XXX XXX	
Telephone:	0508 724687	
Emergency Numbers: Australia: New Zealand:	13 1126 (Poisons Information Centre) 0800 764 766 (National Poison Centre)	
Date of SDS Preparation:	15 November 2018 v2	
Castian 2 Haranda Ta	den tifinetien	

Section 2. **Hazards Identification**

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia

New Zealand:

This substance is hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval No: Surface Coatings and Colourants (Flammable, Toxic [6.7]) -HSR002669

Pictograms



Signal Word: DANGER

HSNO Classification	Hazard Code	Hazard Statement	GHS Category
3.1C	H226	Flammable liquid and vapour.	Flam. Liq. 3

6.1D (inh)	H332	Harmful if inhaled.	Acute Tox. 4
6.1E (oral)	H303	May be harmful if swallowed.	Acute Tox. 5
6.1E (dermal)	H313	May be harmful in contact with skin.	Acute Tox. 5
6.1E (asp)	H304	May be fatal if swallowed and enters airways.	Asp. Tox. 1
6.3A	H315	Causes skin irritation.	Skin Irrit. 2
6.4A	H319	Causes serious eye irritation.	Eye Irrit. 2A
6.5A	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	Resp. Sens. 1
6.5B	H317	May cause an allergic skin reaction.	Skin Sens. 1
6.7B	H351	Suspected of causing cancer.	Carc. 2
6.8B	H361	Suspected of damaging fertility or the unborn child.	Repr. 2
6.9B	H373	May cause damage to organs through prolonged or repeated exposure.	STOT RE 2
9.1D	H401	Toxic to aquatic life.	Aquatic Acute 2
9.3C(NZ only)	H433	Harmful to terrestrial vertebrates.	-

Prevention Code	Prevention Statement
P102	Keep out of reach of children.
P103	Read label before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, sparks, open flames or hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust, fume, gas, mist or vapours.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective clothing.
P281	Use personal protective equipment as required.
P285	In case of inadequate ventilation wear respiratory protection.

Response Code	Response Statement
P101	If medical advice is needed, have product container or label at hand.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P331	Do NOT induce vomiting.
P362	Take off contaminated clothing and wash before re-use.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P303 +	IF ON SKIN (or hair): Remove/Take off immediately all contaminated
P361+P353	clothing. Rinse skin with water/shower.
P304 + P341	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest
	in a position comfortable for breathing.
P305 +	IF IN EYES: Rinse cautiously with water for several minutes. Remove
P351+P338	contact lenses, if present and easy to do. Continue rinsing.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER or
	doctor/physician.
P370 + P378	In case of fire: Use carbon dioxide, foam or dry chemicals for extinction.

Storage Code	Storage Statement
P405	Store locked up.

P501	Dispose of according to Local Regulations or Authorities
------	--

Section 3. Composition / Information on Ingredients

Ingredients	Cas Number	Weight %
Resin	28128-81-2	>60%
1-Methoxy- 2 -propyl acetate	108-65-6	10-30%
Xylene mixture	1330-20-7	10-30%
Ethyl benzene	100-41-4	<3%
Hexamethylene -1,6-diisocyanate	822-06-0	<.05%
OTHER INGREDIENTS DATA		
Chemical characterisation		
Aliphate Polyisocyanate appox: 75% in		
MPA/Xylene [1.1]		

Section 4.	First Aid Measures

Routes of Exposure:

If in Eyes	Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice. Remove contact lenses, if present and easy to do. Continue rinsing.
If on Skin	Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. If skin irritation or rash occurs: get medical advice/attention.
If Swallowed	Rinse mouth. DO NOT induce vomiting. If the victim is conscious give water or milk to drink to dilute the effect. If vomiting occurs, place victim face downwards, with the head turned to the side and lower than the hips to prevent vomit entering the lungs. Seek immediate medical attention.
If Inhaled	Remove person to fresh air. Remove contaminated clothing and loosen remaining clothing. Allow person to assume most comfortable position and keep warm. Keep at rest until fully recovered. Get medical advice if breathing becomes difficult or if you feel unwell.
Most important sy Symptoms:	mptoms and effects, both acute and delayed
Ingestion:	May be harmful if swallowed.
Inhalation:	Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin:	May be harmful in contact with skin. Causes skin irritation. May cause an allergic skin reaction.
Eye:	Causes serious eye irritation.
Chronic:	May be fatal if swallowed and enters airways.
	Suspected of damaging fertility or the unborn child.
	Suspected of causing cancer.
	May cause damage to organs through prolonged or repeated exposure.

Section 5.	Fire Fighting Measures
Hazard Type	Flammable liquid vapours can explode in air if ignited.
Hazards from combustion products	In case of fire, decomposition can produce carbon monoxide isocyanate vapour and traces of Hydrogen cyanide.
Suitable	Extinguishing Media, extinguishing powder, carbon dioxide, Halons and

Extinguishing media	for large fires foam and water spray.
Precautions for firefighters and special protective clothing	Wear full body protection and self-contained breathing apparatus.
HAZCHEM CODE	3Y

Personal precautions:

Wear protective equipment as detailed in Section 8. Clear area of any unprotected personnel. Extinguish all sources of ignition.

Environmental precautions:

Do not discharge into drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Notify authorities if product enters sewers or public waters.

Spill and Disposal procedures:

Absorb the spilt material onto sand, sawdust, earth or other absorbent material. Place in a labelled container and dispose according to Local Regulations.

Section 7.	Handling and Storage	
------------	----------------------	--

Precautions for Handling:

- Read label before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames or hot surfaces. No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use only outdoors or in a well-ventilated area.
- Use explosion-proof electrical/ventilating/lighting.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust, fume, gas, mist or vapours.
- Wash hands thoroughly after handling.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective clothing and equipment.
- In case of inadequate ventilation wear respiratory protection.

Precautions for Storage:

- Store away from incompatible materials listed in Section 10.
- Store locked up, in a well-ventilated place. Keep cool.
- Avoid temperatures above 50°C.
- Product should be stored in properly sealed containers, if at all, not used in one application.
- In tightly sealed containers this can lead to possible bursting of containers.
- Keep out of reach of children.

Section 8	Exposure Controls /	Personal Protection
-----------	---------------------	---------------------

WORKPLACE EXPOSURE STANDARDS (provided for guidance only)

Substance	TWA ppm	mg/m ³	STEL ppm	mg/m³
Xylene	50	217	-	-
Ethyl Benzene	100	434	125	545

Workplace Exposure Standard – Time Weighted Average (WES-TWA). The time-weighted average exposure standard designed to protect the worker from the effects of long-term exposure. Workplace Exposure Standard – Short-Term

Exposure Limit (WESSTEL). The 15-minute average exposure standard. Applies to any 15- Minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and time-weighted average exposures apply. Workplace Exposure Standards and Biological Exposure Indices NOV 2017 9TH EDITION.

Engineering Controls

Use only in well ventilated areas. Introduce local ventilation where necessary.

Personal Protection Equipment



Eyes	Wear safety goggles with side shields.	
Hands and Skin	Wear PVC or rubber gloves. Wear overalls and use barrier cream.	
Respiratory	When spraying wear respiratory mask.	

Section 9 Physical and Chemical Properties		
Appearance	Yellowish liquid	
Odour	Solvent odour	
Odour Threshold	Not applicable	
рН	Not applicable	
Boiling Point	145°C for solvent	
Melting Point	Not applicable	
Freezing Point	Not applicable	
Flash Point	38 ⁰ C(for solvent)	
Flammability	Not applicable	
Upper and Lower	Not applicable	
Exposure Limits		
Volatile Component	40%	
Vapour Pressure 25 ^o C	Not applicable	
Specific Gravity	1.07	
Solubilities	Immiscible	
Partition Coefficient:	Not applicable	
Auto-ignition	Not applicable	
Temperature		
Decomposition	Not applicable	
Temperature		

Section 10. Stability and Reactivity

Stability of SubstanceThis product is stable under normal conditions.	
Conditions to Avoid	Sources of ignition. Heat.
Incompatible Materials	Exothermic reaction with amines and alcohol.
Hazardous Decomposition	carbon monoxide, isocyanate vapour and traces of Hydrogen
Products	cyanide.

Not applicable

Not applicable

Section 11 Toxicological Information

Acute Effects:

Kinematic Viscosity

Particle Characteristics

Swallowed	May be harmful if swallowed.	
Dermal	May be harmful if in contact with skin.	
Inhalation	Harmful if inhaled.	
Eye	Causes severe eye irritation.	

Skin	Causes skin irritation.	May cause an allergic skin reaction.

Chronic Effects:

Carcinogenicity	Suspected of causing cancer.	
Reproductive	Suspected of damaging fertility or the unborn child.	
Toxicity		
Germ Cell	Not applicable.	
Mutagenicity		
Aspiration	May be fatal if swallowed and enters airways.	
STOT/SE	Not applicable.	
STOT/RE	Causes damage to organs through prolonged or repeated exposure.	

Section 12. Ecotoxicological Information

New Zealand:

HSNO Classes:

9.1D = Toxic to aquatic life. 9.3C = Harmful to terrestrial vertebrates.

Persistence and degradability	No data available
Bioaccumulation	No data available
Mobility in Soil	No data available
Other adverse effects	No data available
Precautions	Do not allow to enter waterways.

Section 13. Disposal Considerations

Disposal Method: Place recovered product into an appropriate waste container for disposal through appropriate waste company or specialized landfill in accordance with local regulations. Ensure container is sealed and isolated away from ignition sources.

Precautions: Ensure waste container containing recovered product is labelled "Hazardous Waste – Flammable, Ecotoxic". If triple rinsing container, add rinsate to waste container for disposal.

Disposal methods to avoid: Do not allow to enter waterways.

Section 14

Transport Information

This product is classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code) (7th edition).

This product is classified as a Dangerous Good for transport in NZ ; NZS 5433:2012



<u>Road and Rail Transport</u> UN No: Class-primary Packing Group Proper Shipping Name:	1866 3 III RESIN SOLUTION, FLAMMABLE
<u>Air Transport</u> UN No: Class-primary Packing Group Proper Shipping Name:	1866 3 III RESIN SOLUTION, FLAMMABLE

<u>Marine Transport</u>	
UN No:	1866
Class-primary	3
Packing Group	III
Proper Shipping Name:	RESIN SOLUTION, FLAMMABLE

Limited Quantities Statement:

If the product's individual container is below 5L/kg, it can be transported as a non-DG as long as the product packaging is still labelled as per DG requirements and the driver is given safety information in accordance with Chapter 3.4 of the UNRTDG.

Section 15	Regulatory Information	
------------	------------------------	--

Australia:

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as a **Schedule 5** Poison according to the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).

New Zealand:

This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EPA Approval Code: Surface Coatings and Colourants (Flammable, Toxic [6.7]) - HSR002669

HSNO Classification: 3.1C, 6.1D(inh), 6.1E(oral, asp), 6.3A, 6.5B, 6.7B, 6.8B, 6.9B, 8.3A, 9.1B, 9.3C

HSW (HS) Regulations 2017 and EPA Notices	Trigger Quantity
Certified Handler	Not required
Location Certificate	500L (>5L), 1500L(<5L), 250L open
Tracking Trigger Quantities	Not required
Signage Trigger Quantities	1 000L (3.1C, 9.1B)
Emergency Response Plan	1 000L (9.1B)
Secondary Containment	1 000L (9.1B)
Restriction of Use	Only use for the intended purpose.

Section 16	Other Information	
Glossary		
EC ₅₀	Median effective concentration.	
EEL	Environmental Exposure Limit.	
EPA	Environmental Protection Authority	
HSNO	Hazardous Substances and New Organisms.	
HSW	Health and Safety at Work.	
LC ₅₀	Lethal concentration that will kill 50% of the test organisms	
	inhaling or ingesting it.	
LD ₅₀	Lethal dose to kill 50% of test animals/organisms.	
LEL	Lower explosive level.	
OSHA	American Occupational Safety and Health Administration.	
TEL	Tolerable Exposure Limit.	
TLV	Threshold Limit Value-an exposure limit set by responsible	
	authority.	
UEL	Upper Explosive Level	
WES	Workplace Exposure Limit	

References:

Australia:

1. Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

2. National Industrial Chemicals Notification and Assessment Scheme (NICNAS).

3. Standard for the Uniform Scheduling of Medicines and Poisons.

- 4. Australian Code for the Transport of Dangerous Goods by Road & Rail.
- 5. Model Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.
- 6. Workplace exposure standards for airborne contaminants, Safe work Australia.
- 7. American Conference of Industrial Hygienists (ACGIH).
- 8. Globally Harmonised System of Classification and Labelling of chemicals.

New Zealand:

- 1. EPA Hazardous Substances (Safety Data Sheets) Notice 2017
- 2. Workplace Exposure Standards and Biological Exposure Indices Nov 2017 edition.
- 3. Assigning a hazardous substance to a HSNO Approval (Aug 2013).
- 4. Transport of Dangerous goods on land NZS 5433:2012
- 5. HSW (Hazardous Substances) Regulations 2017

Disclaimer

This document has been prepared by TCC (NZ) Ltd and serves as the suppliers Safety Data Sheet ('SDS'). It is based on information concerning the product which has been provided to TCC (NZ) Ltd or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer. While TCC (NZ) have taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, TCC (NZ) Ltd accept no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS

The information herein is given in good faith, but no warranty, express or implied is made.

Please contact the Australian Manufacturer or New Zealand distributor, if further information is required.

Issue Date:15 November 2018Review Date:15 November 2023