

ULTRA PREMIUM

Solashield Matt

Product Code: MSS

Product Description

Haymes Solashield anti-ageing Surface Lock Technology ensures your home will stay looking good for longer. With superior adhesion and flexibility, the self-priming interlocking barrier coating actively repels mould, dust and dirt. Delivering a long lasting finish, Haymes Solashield provides the ultimate UV defence for all Australian weather conditions.



Product Features

- ✓ Repels dirt and mould
- ✓ Salt resistant
- ✓ Ultimate UV defence
- ✓ Self-priming

Where to use

Masonry, Brick, Render, Fibro, Stone and Concrete.

Not Suitable for use on timber, metal or walk on surfaces.

Typical Properties

Gloss	4 @ 60° 4 @ 85°
Application tools	Brush, roller, spray
Wash up	Water
Dry Time	Touch dry 20 minutes Recoat 2 hours
Coverage	Up to 16m ² /L
Colour	White, UDT, DKT, EDT
Sizes	4L, 10L, 15L
Approvals	APAS 0280/3
VOC	44g/L
Volume solids	37%
Film Build per coat	Wet 62 um Dry 23 um

Surface Preparation

General Surface Preparation	<ol style="list-style-type: none"> 1. Fill cracks, nail holes and imperfections with Haymes Unifill. 2. Scrape all loose/flaking paint. Sand smooth & dust down. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants. 3. Priming may be required on certain substrates.
Previously Painted Surfaces	<ol style="list-style-type: none"> 1. Prepare any damaged areas as for General Surface Preparation. 2. Test for loose paint with adhesive tape. All loose material must be removed prior to painting. 3. Sand gloss surfaces to a dull finish. Remove all dust 4. Remove any chalk by sanding or scouring to a sound surface. 5. For surfaces in good condition no primers or undercoats are required.

Masonry, Brick, Concrete, Render	<ol style="list-style-type: none"> 1. New concrete and cement render must be cured for at least 28 days prior to painting. 2. Wash with a high pressure water washer.
Pre-Cast Concrete	<ol style="list-style-type: none"> 1. Mould release agents must be fully removed prior to painting 2. Clean the surface using Haymes Unikleen solution 3. Rinse using a hot pressure wash 4. Check the surface in several areas for water beading. If water beads cleaning must be repeated until no water beading occurs.

Application

- Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- Do not apply if rain or dew is predicted within 24 hours.
- Stir thoroughly before and during application.
- Apply 2 coats by brush, roller or spray.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.
- Please check the colour for accuracy before application. Haymes Paint will not be accountable for the application of incorrect colours.

Thinning

Thinning is not recommended unless spraying; add up to 100ml clean water per litre of paint to achieve acceptable atomisation. Up to 50ml of clean water can be added per litre of paint to ease application under very warm conditions. Thinning may necessitate additional coats to achieve required film builds.

Care and Maintenance

Regular cleaning of the surface will assist removing dirt, dust and contaminants that will result in a longer coating life.

Storage

Protect from extremes of temperature. Store between 5°C and 30°C.

Warranty

Haymes guarantees that Solashield will not flake, blister or peel for 20 years. For this warranty to apply Solashield must be applied to correctly prepared surfaces. For the warranty to be valid Henry Haymes Pty Ltd must be notified within 14 days of the claimant becoming aware of an alleged fault and within 30 days of the initiation of the alleged fault. Should the alleged fault prove to be due to faulty product to the satisfaction of Henry Haymes Pty Ltd, Henry Haymes Pty Ltd will provide, free of charge, sufficient paint to rectify the affected area. This warranty does not cover failure caused by breakdown of any previous coatings. Haymes will supply paint to recoat affected areas should the product not perform as specified above. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure. Contact Haymes Service Express 1800 033 431

Safety Directions

Keep out of reach of children. Avoid contact with skin and eyes and inhalation of vapour. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using.

First Aid Instructions

If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 1126). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice. If affected by inhalation, remove to fresh air. If breathing difficulty persists or occurs later, consult a doctor.

NOTE: Further information is available in the form of Material Safety Data and Product Information Sheets from your local Distributor or Freecall Haymes Paint on 1800 033 431. We are continually updating materials and methods, so please ensure you have the latest information.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment

This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint (1800 033 431). We are continually updating materials and methods, so please ensure you have the latest information.

Henry Haymes Pty Ltd
A.B.N. 14 004 201 638
Waringa Drive
Wendouree Industrial Estate
Ballarat Vic 3350
Freecall 1800 033 431
Freefax 1800 801 892
www.haymepaint.com.au

Date of Preparation 10/11/14