

# ULTRA PREMIUM PREPCOAT

## Ultralock

Product Code: UPUL

### Product description

Haymes Ultralock is a unique turps-based primer, undercoat and sealer all in one. It is rapid-drying and easy to apply, with superb adhesion and stain sealing properties, including impressive tannin blocking resistance and permanent sealing of tobacco and water stains. Ultralock is ideal for use as a sealer binder for set plaster and has the benefit of being suitable for use under and over both water and solvent-based topcoats, as well as interior and exterior surfaces.



### Key Features

- ✓ Rapid 2 hour recoat
- ✓ Superb adhesion
- ✓ Stain sealer
- ✓ Suitable for interior and exterior

### Where to Use

Suitable for use on a wide variety of Interior & Exterior applications on surfaces including plasterboard, timber, set plaster, PVC, metal, glossy surfaces and pre-painted surfaces. It is suitable for sealing stains such as tobacco, water, mildew, tannin, smoke, pencil and most markers.

### Typical properties

Gloss	3-5 @ 60°
Application tools	Brush, roller, spray
Clean-up	Mineral Turpentine
Dry time	Touch dry 45 mins Recoat 2 hours
Coverage	Up to 16m <sup>2</sup> /L
Colour	White, Tintable to Haymes tinted undercoat formulations
Sizes	1L, 2L, 4L, 10L
VOC	374g/L
Approvals	APAS 0016/1 & 0181
Volume solids	52%
Film build	Wet 63um Dry 33um



Surface Preparation	
General surface preparation	<ol style="list-style-type: none"> <li>1. Fill cracks, nail holes and imperfections with Haymes Unifill.</li> <li>2. Scrape all loose/flaking paint. Sand smooth &amp; dust down.</li> <li>3. All surfaces must be clean, bare, dry and free of wax, grease and other contaminants.</li> </ol>
Previously painted surfaces	<ol style="list-style-type: none"> <li>1. Prepare any damaged areas as for General Surface Preparation.</li> <li>2. Sand gloss surfaces to a dull finish. Remove all dust.</li> </ol>
Plasterboard and set plaster	<ol style="list-style-type: none"> <li>1. Prepare any damaged areas as for General Surface Preparation.</li> <li>2. Remove all dust.</li> </ol>
Timber	<ol style="list-style-type: none"> <li>1. Prepare any damaged areas as for General Surface Preparation.</li> <li>2. Sand greyed or weathered timber to a sound renewed surface.</li> </ol>
Masonry, brick, concrete, render	<ol style="list-style-type: none"> <li>1. New concrete and render must be cured for at least 28 days prior to painting.</li> <li>2. Wash with Haymes Unikleen &amp; rinse with clean water.</li> <li>3. Apply one coat of Haymes Ultraseal.</li> </ol>
Metal	<ol style="list-style-type: none"> <li>1. Prepare any damaged areas as for General Surface Preparation.</li> <li>2. Remove loose rust and treat any remaining rust with a rust converter.</li> <li>3. On zinc treated surfaces apply 1 coat of Haymes Ultracover.</li> <li>4. For corrosion prevention apply 1 coat of Haymes Ultraprime</li> </ol>

Application
<p>Do NOT apply if ambient temperature is less than 10°C or greater than 30°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to Thinning advice.</p> <ul style="list-style-type: none"> <li>• Stir thoroughly before and during application.</li> <li>• Apply 1 coat by brush, roller or spray.</li> <li>• All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity drying times will be extended.</li> </ul>

Thinning
<p>Thinning is not recommended unless spraying- add up to 100ml clean turps per litre of paint to achieve acceptable atomisation. Under very warm conditions, up to 50ml of turps can be added per litre of paint to ease application.</p>

Storage
<p>Protect from extremes of temperature. Store between 5°C and 30°C.</p>

Safety & First Aid
<p>Read label before use. Keep out of reach of children. Flammable liquid and vapour. Harmful if inhaled. May cause drowsiness or dizziness. Avoid breathing vapours. IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Harmful in contact with skin. Causes skin irritation. IF ON SKIN OR HAIR: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash skin with plenty of soap and water. If skin irritation occurs get medical advice. IF IN EYES: Wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice. Harmful if swallowed. IF SWALLOWED: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water. If symptoms develop or persist seek medical advice. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection. Wash exposed skin thoroughly after handling.</p>

Dangerous Goods Classification	
 <p>Flammable Class 3 Packaging Group III UN1263 PAINT</p>	 <p>Warning</p>

Protect our environment
DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Manufacturer's comment
This product has been designed as part of a totally integrated application system. Use with any other manufacturer's product(s) or failing to follow application instructions, could result in detrimental effects on product performance, for which Henry Haymes Pty. Ltd. cannot be held responsible. Further information is available in the form of Safety Data and Product Information Sheets from Haymes Paint <a href="http://www.haymespaint.com.au">www.haymespaint.com.au</a> . We are continually updating materials and methods, so please ensure you have the latest information.

Disclaimer
The information provided is correct at the time of preparation; however it is the responsibility of those using this information to check that it is current prior to specifying, recommending or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices are in compliance with applicable laws and other government enactments. Haymes Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Haymes Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded.

Henry Haymes Pty Ltd  
A.B.N. 14 004 201 638  
Waringa Drive  
Wendouree Industrial Estate  
Ballarat Vic 3350  
Free call 1800 033 431  
Free fax 1800 801 892  
[www.haymespaint.com.au](http://www.haymespaint.com.au)

**Date of Preparation**      21/09/2016