

AD- VF101sm kit
fiber-optic video transceivers

Our fiber-optic video transceivers can simultaneously transmit 1-64 channels of 8 bit digitally encoded video / return or bidirectional data / unidirectional or bidirectional audio / Ethernet / Telephone / Dry contact over one multimode or single-mode optical fiber. These multiplexers are typically used in applications where the cameras have P/T/Z capabilities. Plug and Play design ensures the ease of installation and operation. Electronic and optical adjustments are never required. LED indicators are provided for instantly monitoring system status. Devices are available for either standalone or rack-mount installation ,which is suitable for different working environment .

PRODUCT CHARACTERISTICS

- ◆ 8 bit digitally encoded and non-compression video transmission
- ◆ Directly compatible with NTSC, PAL, and SECAM CCTV camera systems and support RS-232, RS-422, and RS-485 data protocols
- ◆ Support any high-resolution video signal
- ◆ Video AGC support .
- ◆ Automatic compatible PAL, NTSC and SECAM video system
- ◆ Power supply and other parameter state indication, which can monitor the operation condition of system
- ◆ Support no-damage regenerative trunk of video
- ◆ Constant input optical power, and large dynamic range ,no Electrical or Optical Adjustments Required .
- ◆ Special ASIC design .
- ◆ Industry-grade of operating temperature from -10° to 75° , which is applied to the different working environment
- ◆ Hot-swap function
- ◆ Stand-alone type or card-type installed in 19" 2U or 4U rack-mount chassis.

fiber-optic video transceivers Part No. AD-VF101sm-kit	
Technical Specification	
Video channels	1 channel
Video bandwidth	8 MHz
Automatic compatible video system	PAL、NTSC、SECAM
Video input / output impedance	75 Ω

Video signal-to-noise ratio	≥67dB	
Differential gain	(10%-90%APL) DG <1% (typical value)	
Differential phase	(10%-90%APL) DP <0.7° (typical value)	
Video connector	BNC	
Fiber-optic Specification	F/O connector: FC/ST/SC Transmitter : Tx Power:-8 ~ -3dBm Sensitivity : ≤-35dBm Receiver: Tx Power:-15 ~ -8dBm Sensitivity : ≤-24dBm Transmission Distance :20KM (single mode) 550m(multi mode) Operating Wavelength: TX1310/RX1550nm (Transmitter); TX1550/RX1310nm (Receiver)	
Specification of custom-made options		
Data	Connector: Terminal Blocks Encoded type : RS485 / RS422 / RS232 / Manchester Data rate : 0 - 400Kbps BER: ≤10 ⁻⁹	
Audio	Connector: Terminal Blocks Audio input / output impedance :600Ω(Balance/ unbalance) Audio input / output voltage :2Vp-p (typical value) Audio input / output level :0dBm (typical value) Video bandwidth:10HZ~12KHZ Audio digital encoded bandwidth :24bit Audio signal-to-noise ratio: S/N≥95dB (weighted)	
Telephone	Connector: RJ11 Bandwidth :8KHZ Features: Support call-showing function ;support H-F Operating mode : Point to point hotline mode / FXS-FXO	
Ethernet	Connector: RJ45 Support mode : Half duplex or Full duplex Standards: IEEE802.3 Data rate : 10M / 100Mbps Bandwidth: 25M	
Dry contact	Input voltage :-7~12V Input current:0.04MA Output current:<1A Output volatage:<500V	



Operating Voltage: DC5V (we will offer external power supply from AC96-240V to DC5V for each unit)

Operating Temperature: -10°C to +75°C

Storing Temperature : -55°C to +85°C

Humidity: 0 to 95% non-condensing

MTBF : $\geq 10^5$ hours

Warranty : 3 years

Application :

Intelligent Transportation System

Connection of Sub-network for Surveillance Center

Public Security Surveillance

High Way & Toll Station Surveillance

Industrial Closed Circuit Television Surveillance