

2 Ports USB DVI KVM with USB 2.0 HUB & Audio

Model: ADT-221DU

Specification Introduction

Thank you for purchasing of 2 **Ports USB DVI KVM with USB 2.0 HUB and Audio.** You now have a high quality and durability system to control multiple computers/servers from one console (Mouse, Keyboard, Monitor, Microphone and Speaker).

Features

- 1. Controls 2 computers from single console (keyboard/mouse) over USB connection by using standard USB cables.
 - 2. Supports USB keyboard/mouse.
 - 3. Compliant with USB Specification Revision 2.0 and USB Device Class Definition for HID Revision 1.11.
 - 4. Support 2 USB downstream ports.
 - 5. 2 computers can share 2 USB downstream ports.
 - 6. Supports 2 types of switching: a. Push button on front panel, Hot-keys on USB keyboard.
 - 7. LED display for easy status monitoring.
 - 8. Power status of connected computer.
 - 9. Active host computer.
 - 10. Supply Microsoft Intellimouse 3 ~ 5 Key Mouse & Microsoft Natural Keyboard Pro series.
 - 11. Supports DVI-I interface.
 - 12. Supports WUXGA resolutions up to 1920 x 1200 @ 60HZ.
 - 13. Support Windows 98/98SE/2000/Me/XP/VISTA/7, Linux ,Mac OS9/OSX, SunMicro Solaris 8 or later.
 - 14. Provide HUB switching in independent method or combination with the host switching (USB HUB Auto-Switch mode).
 - 15. Supports Auto-Scan function (Time interval can be adjusted between 5-20 seconds when the Auto-Scan function is enabled).
 - 16. Provides audio switching in independent method.



11. Specifications

	Sp	pecification
Number Of Computer Controlled		2
Selection Method		Push Button/Hot Key
LEDs		Host Selected LED (RED)
		HUB Selected LED (Green)
		Auto Switch & Auto Scan LED (Green)
Compliant with USB Version		USB1.0 / USB1.1 / USB2.0
Compliant with HID Version		USB HID 1.11
PC Connectors	Video	2 x DVI-I WUXGA female
	USB	2 x USB Type B female
	Microphone	2 x Audio Jack Female (Pink)
	Speaker	2 x Audio Jack Female (Green)
Console port	Video	1 x DVI-D WUXGA female
	Keyboard	2 x USB Type A female
	Microphone	1 x Audio Jack Female (Pink)
	Speaker	1 x Audio Jack Female (Green)
USB Downstream ports		2 x USB Type A female
Auto-Scan Interval		5,10,15,20 sec
Supports resolution		Max. Resolution: 1920x1200 @60Hz
Operating system supported		Win 98/98SE/ME/2000/XP/Vista/7, Mac OS9/X, Linux, Sun Micro OS
Cables Included		2 sets of USB, DVI and audio cable
Cable Length		1.8M
Power		By External Adaptor
Output Voltage		5V
Output Current		2A
Hot Pluggable		Yes
Dimensions (LxWxH)		170 x 82 x 44 mm
Unit Weight		700 g



