

## 2 Ports USB KVM with USB 2.0 HUB & Audio

Model: ADT-221UA

### Introduction

Thank you for purchasing of **2 Ports USB KVM with USB 2.0 HUB and Audio**. You now have a high quality and durability system to control multiple computers/servers from one console (Mouse, Keyboard, Monitor, Microphone and Speaker).

### Features

1. Controls 2 computers from single console (keyboard/mouse) over USB connection by using standard USB cables.
2. Supports USB keyboard/mouse.
3. Compliant with USB Specification Revision 2.0 and USB Device Class Definition for HID Revision 1.11.
4. Support 2 USB downstream ports.
5. 2 computers can share 2 USB downstream ports.
6. Supports 2 types of switching: a. Push button on front panel, Hot-keys on USB keyboard.
7. LED display for easy status monitoring.
8. Power status of connected computer.
9. Active host computer.
10. Supply Microsoft Intellimouse 3 ~ 5 Key Mouse & Microsoft Natural Keyboard Pro series.
11. Supports VGA resolutions up to 2048X1536 @ 85MHZ.
12. Support Windows 98/98SE/2000/Me/XP/VISTA/7, Linux ,Mac OS9/OSX, SunMicro Solaris 8 or later.
13. Provide HUB switching in independent method or combination with the host switching (USB HUB Auto-Switch mode).
14. Supports Auto-Scan function (Time interval can be adjusted between 5-20 seconds when the Auto-Scan function is enabled).
15. Provides audio switching in independent method.

## 16. Specifications

| Specification                 |   |                               |
|-------------------------------|---|-------------------------------|
| Number Of Computer Controlled | 2   |                               |
| Selection Method              | Push Button/Hot Key   |                               |
| LEDs                          | HUB Switch LED ( Green)   |                               |
|                               | PC Host LED (RED)   |                               |
|                               | Auto Switch & Auto Scan LED (Green)                               |                               |
| Compliant with USB Version    | USB1.0 / USB1.1 / USB2.0  |                               |
| Compliant with HID Version    | USB HID 1.11  |                               |
| PC Connectors                 | Video   | 2 x HDB-15 male               |
|                               | USB   | 2 x USB Type B female         |
|                               | Microphone  | 2 x Audio Jack Female (Pink)  |
|                               | Speaker   | 2 x Audio Jack Female (Green) |
| Console port                  | Video   | 1 x HDB-15 female             |
|                               | Keyboard/Mouse  | 2 x USB Type A female         |
|                               | Microphone  | 1 x Audio Jack Female (Pink)  |
|                               | Speaker   | 1 x Audio Jack Female (Green) |
| USB Downstream ports          | 2 x USB Type A female   |                               |
| Auto-Scan Interval            | 5,10,15,20 sec  |                               |
| DDC, DDC2 monitor             | Yes(Max.Resolution: 1920x1200 @60Hz)                              |                               |
| Operating system supported    | Win 98/98SE/ME/2000/XP/Vista/7,<br>Mac OS9/X, Linux, Sun Micro OS |                               |
| Cables Included               | 2 sets of USB, VGA and audio cable                                |                               |
| Cable Length                  | 1.8M  |                               |
| Power                         | By External Adaptor   |                               |
| Output Voltage                | 5V  |                               |
| Output Current                | 2A  |                               |
| Hot Pluggable                 | Yes   |                               |
| Dimensions (LxWxH)            | 170 x 82 x 44 mm  |                               |
| Unit Weight                   | 685g  |                               |

