

4Ports USB DVI KVM with USB 2.0 HUB & Audio

Model: ADT-241DU

Specification

Introduction

Thank you for purchasing of **4 Ports USB DVI KVM with USB 2.0 HUB and Audio**. You now have a high quality and durability system to control multiple computers/servers from one console (Mouse, Keyboard, Monitor, Microphone and Speaker).

Features

1. Controls 4 computers from single console (keyboard/mouse) over USB connection by using standard USB cables.
2. Supports USB keyboard/mouse.
3. Compliant with USB Specification Revision 2.0 and USB Device Class Definition for HID Revision 1.11.
4. Support 2 USB downstream ports.
5. 4 computers can share 2 USB downstream ports.
6. Supports 2 types of switching: a. Push button on front panel, Hot-keys on USB keyboard.
7. LED display for easy status monitoring.
8. Power status of connected computer.
9. Active host computer.
10. Supply Microsoft Intellimouse 3 ~ 5 Key Mouse & Microsoft Natural Keyboard Pro series.
11. Supports DVI-I interface.
12. Supports WUXGA resolutions up to 1920 x 1200 @ 60HZ.
13. Support Windows 98/98SE/2000/Me/XP/VISTA/7, Linux ,Mac OS9/OSX, SunMicro Solaris 8 or later.
14. Provide HUB switching in independent method or combination with the host switching (USB HUB Auto-Switch mode).
15. Supports Auto-Scan function (Time interval can be adjusted between 5-20 seconds when the Auto-Scan function is enabled).
16. Provides audio switching in independent method.

11. Specifications

Specification		
Number Of Computer Controlled	4	
Selection Method	Push Button/Hot Key	
LEDs	Host Selected LED (RED)	
	HUB Selected LED (Green)	
	Auto Switch & Auto Scan LED (Green)	
Compliant with USB Version	USB1.0 / USB1.1 / USB2.0	
Compliant with HID Version	USB HID 1.11	
PC Connectors	Video	4 x DVI-I WUXGA female
	USB	4 x USB Type B female
	Microphone	4 x Audio Jack Female (Pink)
	Speaker	4 x Audio Jack Female (Green)
Console port	Video	1 x DVI-D WUXGA female
	Keyboard	2 x USB Type A female
	Microphone	1 x Audio Jack Female (Pink)
	Speaker	1 x Audio Jack Female (Green)
USB Downstream ports	2 x USB Type A female	
Auto-Scan Interval	5,10,15,20 sec	
Supports resolution	Max. Resolution: 1920x1200 @60Hz	
Operating system supported	Win 98/98SE/ME/2000/XP/Vista/7, Mac OS9/X, Linux, Sun Micro OS	
Cables Included	4 sets of USB, DVI and audio cable	
Cable Length	1.8M	
Power	By External Adaptor	
Output Voltage	5V	
Output Current	2A	
Hot Pluggable	Yes	
Dimensions (LxWxH)	200 x 82 x 44 mm	
Unit Weight	915 g	

