

ADVICE OGMKS Plus 2KVA/3KVA Inverter

Expert MKS plus is similar to Expert MKS series but with bigger MPPT solar charge controller. Besides, it's worry-free to start up motor-type loads such as refrigerators, motors, pumps, compressors and laser printers as well as electronic loads like TV's, Computers, power tool and battery chargers.

Features:

- Pure sine wave inverter
- Built-in MPPT solar charge controller
- Selectable input voltage range for home appliances and personal computers
- Selectable charging current based on applications
- Configurable AC/Solar input priority via LCD setting
- Compatible to mains voltage or generator power
- Auto restart while AC is recovering
- Overload and short circuit protection
- Smart battery charger design for optimized battery performance
- Cold start function
- Optional remote panel available



Specifications

Model	OGMKS2KVA-Plus-24	OGMKS2KVA-Plus-48	OGMKS3KVA-Plus-24	OGMKS3KVA-Plus-48
RATED POWER	2000VA/1600W	2000VA/1600W	3000VA/2400W	3000VA/2400W
INPUT				
Voltage	120 VAC or 230 VAC		230 VAC	
Selectable Voltage Range	95-140 VAC or 170-280 VAC (For Personal Computers) 65-140 VAC or 90-280 VAC (For Home Appliances)		170-280 VAC (For Personal Computers) 90-280 VAC (For Home Appliances)	
Frequency Range	50 Hz/60 Hz (Auto sensing)			
OUTPUT				
AC Voltage Regulation (Batt. Mode)	110/120 VAC \pm 5% (User selectable) or 230VAC \pm 5%		230VAC \pm 5%	
Surge Power	4000VA		6000VA	
Efficiency (Peak)	90% - 93%			
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)			
Waveform	Pure sine wave			
BATTERY				
Battery Voltage	24 VDC	48 VDC	24 VDC	48 VDC
Floating Charge Voltage	27 VDC	54 VDC	27 VDC	54 VDC
Overcharge Protection	31 VDC	62 VDC	31 VDC	62 VDC
SOLAR CHARGER & AC CHARGER				
Max. PV Array Power	1500 W	3000 W	1500 W	3000 W
MPPT Range @ Operating Voltage	30~115 VDC	60~115 VDC	30~115VDC	60~115 VDC
Max. PV Array Open Circuit Voltage	145 VDC			
Max.Solar Charge Current	60A			
Max. AC Charge Current	20A or 30A	10A or 15A	30A	15A
Max. Efficiency	98%			
Standby Power Consumption	2 W			
PHYSICAL				
Dimension, D x W x H (mm)	140 x 295 x 479			
Net Weight (kgs)	11.5			
OPERATING ENVIRONMENT				
Humidity	5% to 95% Relative Humidity(Non-condensing)			
Operating Temperature	0°C to 55°C			
Storage Temperature	-15°C to 60°C			

Product specifications are subject to change without further notice.