

## Outdoor power cabinet

The Type 2 cabinet platform is designed for a variety of applications and can be tailored to fit your specific needs. The cabinet is well suited for power, batteries and telecom/industrial equipment, all integrated into a robust package.



# TYPE 2

## OUTDOOR CABINET

Doc 234747.DS3 – rev8

### RELIABILITY

Reliability within the outdoor plant depends upon a cool, dry and secure environment for the electronics such as the DC power, Telecom and Industrial equipment. The Type 2 Outdoor Power Cabinet more than accomplishes this with a variety of Thermal Management solutions that will keep sensitive electronics functioning in the most extreme environments.



### APPLICATIONS

The Type 2 cabinet is well suited for a wide range of Telecom and Industrial applications such as:

- Radio Access Networks (2G, 3G, 4G / LTE / WiMax)
- Optical Networks
- Cable TV
- DSL
- SCADA
- Rail and Metro
- Power distribution

The cabinet works very well as a stand-alone power / battery backup solution and provides additional space for telecom / Industrial equipment. In addition the outdoor enclosure is suited for Industrial environments.

### KEY FEATURES

- 19" EQUIPMENT SPACE
- OPTIONAL THERMAL INSULATION
- DC POWER, TELECOM/INDUSTRIAL EQUIPMENT AND BATTERY BACKUP
- ALUMINUM CONSTRUCTION
- DOOR MOUNTED THERMAL MANAGEMENT OPTIONS:
  - FAN / FILTER
  - AIR-CONDITIONER
- FLOOR, WALL OR POLE MOUNT
- 3U SECTION FOR A DIN RAIL AC DISTRIBUTION
- UL 50
- IP55, NEMA 3R
- CLOGGED FILTER DETECTION
- EASY INSTALLATION
- EASY FILTER CHANGE
- EASY MAINTENANCE

# TYPE 2

## OUTDOOR CABINET



Model	15U F/F	15U Air-con	22U F/F	22U Air-con
<b>PHYSICAL SPECIFICATIONS</b>				
Exterior Height (mm)	743 (29.3")	743 (29.3")	1047,5 (41,2")	1047,5 (41,2")
Exterior Width (mm)	586 (23,1")	586 (23,1")	586 (23,1")	586 (23,1")
Exterior Depth (mm)	580 (22,8")	790 (31,1")	580 (22,8")	790 (31,1")
Net weight (Kg)	28,4kg (62,6lbs)	48,4kg (106,7lbs)	32,4kg (71,5lbs)	52,4kg (115,5lbs)
Usable Mounting Height	12U (533mm / 21.0")	12U (533mm / 21.0")	19U (844mm / 33")	19U (844mm / 33")

### All Models

### CONSTRUCTION SPECIFICATIONS

Skin material	1.5mm (0.06") thick aluminum (lightweight, corrosion-resistant)
Frame Material	Galvanized Steel
Powder-Coat Paint	Outdoor Polyester light gray RAL 7035 coating
Insulation	Closed Cell Insulation (optional)
Rail mounting Pattern	EIA Standard with holes for Cage nuts
Orientation	19" mount

### DOOR SPECIFICATIONS

Latches	Two point latch, with optional euro lock cylinder
Gasket	UL rated for outdoor use
Door Stop / Door Stay	Wind latch to hold door during maintenance (120°)
Fan and Filter Solution	Filter class F5 (EN 779),
Air Conditioning Unit	570W at 50Hz and 35C/35C

### MISC. SPECIFICATIONS AND OPTIONS

Cable Glands	Bottom Cable Access	Different options available
Battery trays	19" tray(s) Space: 448,5mm W x 398mm D (17,6" W x 15,6" D) Max. 150kg (330 lbs) weight load	Each Tray weighs 2.1kg (4.6lbs)
Ground Bar	4xM6 inserts on 19" rails, left/right	
Heater	Optional 400W	Kit weighs 1.3kg (2.9lbs)
Plinth	Optional 152mm (6") high plinth. Foot Print: 579mm W x 502mm D (22,8" W x 19,8" D)	Weights 7.6kg (16.7lbs)
Mounting Brackets	Stainless Steel wall or pole Pole diameter Ø 60-115mm Max 200Kg (441lbs) weight load	Weights 11kg (24.2lbs)
Lifting Ears	4 Detachable sheet metal ears connected with 4 x M8 bolts	
Packaging Information	Shipments made in an upright position on a wood pallet	Weights 7kg (15.4lbs)

### DESIGN STANDARDS

Electrical	IEC 60950, UL 60950*, CAN CSA-C22.2 No. 60950-1-03 (Depending on Equipment Installed)
EMC	ETSI EN 300 386 V.1.3.1, EN 61000-6-3, EN 61000-6-2
Environment	ETS 300 019, Ingress Protection: EN 60529 IP55

Doc 234747.DS3 – rev8

Specifications are subject to change without notice

Advice Electronics Ltd

Advice Building, 16 Atir Yeda St., Kfar Saba, 4464321, Israel • Tel: +972-3-9000910 • sales@advice.co.il • www.advice.co.il