

OUTDOOR-UPS

The Advice ALL IN ONE outdoor ups at IP54 polyester enclosures is a smart compact and reliable ups with industry leading design and wide range of temperature operation

Features:

- Light weight and compact industrial design
- Wall hanging coordinator
- 1146 Joule surge protection- Exclusive
- Forced ventilation with adjust thermostat
- waterproof IP54
- Wide operation temperature range 0-65
- Cold start capability
- Surge protection
- Maintenance socket
- USB communication port
- Dry contacts (optional)
- SNMP - (optional)



Specifications

MODEL	CO-UPS-100W-3H	CO-UPS-200W-3H
Load / backup time	100 WATT / 3 Heure	200 WATT / 3 Heure
INPUT		
Voltage	110-300VAC	
Frequency	40-70 Hz	
OUTPUT		
Voltage battery mode	230±1%	
Frequency (on Battery)	(50/60±0.1)Hz	
Transfer Time	Zero	
Waveform	Pure Sinewave	
PROTECTION		
Overload protection	Line mode: switch to bypass, backup mode, shut down	
Short circuit protection	UPS output cut off immediately	
BATTERY		
Type	Sealed, maintenance-free lead acid battery	
Typical recharge time	8 hours to 90% capacity after full discharge	
GENERAL		
Dimension (WxDxH)	650mm x 500mm x 250mm	
Product weight	37 kg	56 kg
Elevation	<1500m	
Operating temperature	0°C to 65 °C	
Storage temperature	-15 °C to +65 °C	
Humidity	20~90% RH @ 0~40 C (non-condensing)	